

Jinbo Marine

Marine Stores & Equipment Datasheet

IMPA DATASHEET

23 - RIGGING EQUIPMENT & GENERAL DECK

Straight Shackle-SB with Hexagon Head Bolt

IMPA CODE

230143

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

Key Product Information

| | | | |
|----------------------|--|---------------------|--|
| IMPA | 230143 | Product Name | Straight Shackle-SB with Hexagon Head Bolt |
| Specification | Body Diam:85mm,Opening:128mm,Thread Bolt and Nut:M90×6,Clear Lenght:289mm,Pin Diam:102mm,S.W.L.:45.0 Ton | Unit | pc |
| Category | 23 - Rigging Equipment & General Deck | Origin | China |

Description

Drop forged carbon steel shackle with a hexagon,metric coarse threaded bolt,which has a split pin hole at the end and a securing nut.

Related IMPA Products

| IMPA | Name | Specification | Unit |
|---------|--|--|------|
| 2301 21 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:20mm,Opening:31mm,Thread Bolt and Nut:M24,Clear Lenght:68mm,Pin Diam:24mm,S.W.L.:2.5Ton | pc |
| 2301 22 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:22mm,Opening:34mm,Thread Bolt and Nut:M24,Clear Lenght:75mm,Pin Diam:24mm,S.W.L.:3.0 Ton | pc |
| 2301 23 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:24mm,Opening:39mm,Thread Bolt and Nut:M30,Clear Lenght:81mm,Pin Diam:30mm,S.W.L.:3.6 Ton | pc |
| 2301 24 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:26mm,Opening:41mm,Thread Bolt and Nut:M30,Clear Lenght:88mm,Pin Diam:32mm,S.W.L.:4.2 Ton | pc |
| 2301 25 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:28mm,Opening:43mm,Thread Bolt and Nut:M33,Clear Lenght:95mm,Pin Diam:34mm,S.W.L.:4.8 Ton | pc |

| IMPA | Name | Specification | Unit |
|------------|--|---|------|
| 2301 26 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:30mm,Opening:45mm,Thread Bolt and Nut:M36,Clear Lenght:102mm,Pin Diam:36mm,S.W.L.:5.4 Ton | pc |
| 2301 27 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:32mm,Opening:48mm,Thread Bolt and Nut:M36,Clear Lenght:109mm,Pin Diam:38mm,S.W.L.:6.2 Ton | pc |
| 2301 28 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:34mm,Opening:50mm,Thread Bolt and Nut:M39,Clear Lenght:116mm,Pin Diam:40mm,S.W.L.:7.0 Ton | pc |
| 2301 29 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:36mm,Opening:54mm,Thread Bolt and Nut:M42,Clear Lenght:123mm,Pin Diam:42mm,S.W.L.:8.0 Ton | pc |
| 2301 30 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:38mm,Opening:57mm,Thread Bolt and Nut:M45,Clear Lenght:129mm,Pin Diam:46mm,S.W.L.:9.0 Ton | pc |
| 2301 31 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:40mm,Opening:60mm,Thread Bolt and Nut:M48,Clear Lenght:136mm,Pin Diam:48mm,S.W.L.:10 Ton | pc |
| 2301 32 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:42mm,Opening:63mm,Thread Bolt and Nut:M48,Clear Lenght:142mm,Pin Diam:51mm,S.W.L.:11 Ton | pc |
| 2301 33 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:44mm,Opening:66mm,Thread Bolt and Nut:M48,Clear Lenght:149mm,Pin Diam:54mm,S.W.L.:12.0 Ton | pc |
| 2301 34 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:46mm,Opening:68mm,Thread Bolt and Nut:M48,Clear Lenght:156mm,Pin Diam:56mm,S.W.L.:13.0 Ton | pc |
| 2301 35 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:48mm,Opening:72mm,Thread Bolt and Nut:M56,Clear Lenght:163mm,Pin Diam:58mm,S.W.L.:14.0 Ton | pc |
| 2301 36 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:50mm,Opening:75mm,Thread Bolt and Nut:M56,Clear Lenght:170mm,Pin Diam:60mm,S.W.L.:15.0 Ton | pc |
| 2301 37 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:55mm,Opening:83mm,Thread Bolt and Nut:M64,Clear Lenght:187mm,Pin Diam:65mm,S.W.L.:18.0 Ton | pc |
| 2301 38 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:60mm,Opening:90mm,Thread Bolt and Nut:M64,Clear Lenght:205mm,Pin Diam:70mm,S.W.L.:22.0 Ton | pc |
| 2301 39 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:65mm,Opening:98mm,Thread Bolt and Nut:M72×6,Clear Lenght:221mm,Pin Diam:77mm,S.W.L.:26.0 Ton | pc |
| 2301 40 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:70mm,Opening:105mm,Thread Bolt and Nut:M80×6,Clear Lenght:238mm,Pin Diam:83mm,S.W.L.:30.0 Ton | pc |
| 2301 41 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:75mm,Opening:112mm,Thread Bolt and Nut:M80×6,Clear Lenght:255mm,Pin Diam:90mm,S.W.L.:35.0 Ton | pc |
| 2301 42 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:80mm,Opening:120mm,Thread Bolt and Nut:M90×6,Clear Lenght:272mm,Pin Diam:96mm,S.W.L.:40.0 Ton | pc |
| 2301 44 | Straight Shackle-SB with Hexagon Head Bolt | Body Diam:90mm,Opening:135mm,Thread Bolt and Nut:M100×6,Clear Lenght:306mm,Pin Diam:108mm,S.W.L.:50.0 Ton | pc |