

Jinbo Marine

Marine Stores & Equipment Datasheet

IMPA DATASHEET

35 - HOSE & COUPLINGS

P.V.C. Steel Coil Reinforced Hose

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

IMPA CODE

350353

Key Product Information

IMPA	350353	Product Name	P.V.C. Steel Coil Reinforced Hose
Specification	Norminal I.D.:8.0mm, Actual O.D.:13.5mm,Working Pressure:13kgf/cm2,Weight Per Mtr:120grm,Mtr Per Coil:50	Unit	
Category	35 - Hose & Couplings	Origin	China

Description

Features: Ample flexibility.High external pressure resistance.Good transparency and smooth internal surface.
Applications: As oil hose for machine tools.As pressure pipe or suction pipe for various pulverised materials.To be used in 65C is recommendable.

Related IMPA Products

IMPA	Name	Specification	Unit
350351	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:4.0mm, Actual O.D.:9.0mm,Working Pressure:15kgf/cm2,Weight Per Mtr:70grm,Mtr Per Coil:50	
350352	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:6.0mm, Actual O.D.:11.0mm,Working Pressure:15kgf/cm2,Weight Per Mtr:90grm,Mtr Per Coil:50	
350354	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:9.0mm, Actual O.D.:15.0mm,Working Pressure:13kgf/cm2,Weight Per Mtr:150grm,Mtr Per Coil:50	
350355	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:10.0mm, Actual O.D.:16.0mm,Working Pressure:10kgf/cm2,Weight Per Mtr:160grm,Mtr Per Coil:50	
350356	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:12.0mm, Actual O.D.:18.0mm,Working Pressure:10kgf/cm2,Weight Per Mtr:185grm,Mtr Per Coil:50	
350357	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:15.0mm, Actual O.D.:22.0mm,Working Pressure:7kgf/cm2,Weight Per Mtr:265grm,Mtr Per Coil:50	

IMPA	Name	Specification	Unit
3503 58	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:19.0mm, Actual O.D.:26.0mm,Working Pressure:7kgf/cm2,Weight Per Mtr:325gm,Mtr Per Coil:50	
3503 59	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:25.0mm, Actual O.D.:33.0mm,Working Pressure:6kgf/cm2,Weight Per Mtr:475gm,Mtr Per Coil:50	
3503 60	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:32.0mm, Actual O.D.:41.0mm,Working Pressure:6kgf/cm2,Weight Per Mtr:670gm,Mtr Per Coil:40	
3503 61	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:38.0mm, Actual O.D.:48.0mm,Working Pressure:6kgf/cm2,Weight Per Mtr:875gm,Mtr Per Coil:40	
3503 62	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:50.0mm, Actual O.D.:62.0mm,Working Pressure:5kgf/cm2,Weight Per Mtr:1,360gm,Mtr Per Coil:40	
3503 63	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:63.0mm, Actual O.D.:80.0mm,Working Pressure:5kgf/cm2,Weight Per Mtr:2,250gm,Mtr Per Coil:20	
3503 64	P.V.C. Steel Coil Reinforced Hose	Norminal I.D.:75.0mm, Actual O.D.:92.0mm,Working Pressure:3kgf/cm2,Weight Per Mtr:3gm,Mtr Per Coil:20	