

**Jinbo Marine**

Marine Stores &amp; Equipment Datasheet

IMPA DATASHEET

**73 - PIPE & TUBE FITTINGS****DIN2532-Cast Iron Flange(10kgf/cm2)**

IMPA CODE

**734535**

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

**Key Product Information**

<b>IMPA</b>	734535	<b>Product Name</b>	DIN2532-Cast Iron Flange(10kgf/cm2)
<b>Specification</b>	Diam.:250mm , O.D.:395mm,Thick:28mm,P.O.D.: 350mm,Bolt Hole No.:12,Thread:M20,Diam.:22mm	<b>Unit</b>	pc
<b>Category</b>	73 - Pipe & Tube Fittings	<b>Origin</b>	China

**Description**

Nominal pressure: 10kgf/cm2

**Related IMPA Products**

IMPA	Name	Specification	Unit
73452 1	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:10mm , O.D.:90mm,Thick:14mm,P.O.D.:60mm,Bolt Hole No.:4,Thread:M12,Diam.:14mm	pc
73452 2	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:15mm , O.D.:95mm,Thick:14mm,P.O.D.:65mm,Bolt Hole No.:4,Thread:M12,Diam.:14mm	pc
73452 3	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:20mm , O.D.:105mm,Thick:16mm,P.O.D.:75mm,Bolt Hole No.:4,Thread:M12,Diam.:14mm	pc
73452 4	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:25mm , O.D.:115mm,Thick:16mm,P.O.D.:85mm,Bolt Hole No.:4,Thread:M12,Diam.:14mm	pc
73452 5	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:32mm , O.D.:140mm,Thick:18mm,P.O.D.:100mm,Bolt Hole No.:4,Thread:M16,Diam.:18mm	pc
73452 6	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:40mm , O.D.:150mm,Thick:18mm,P.O.D.:110mm,Bolt Hole No.:4,Thread:M16,Diam.:18mm	pc
73452 7	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:50mm , O.D.:165mm,Thick:20mm,P.O.D.:125mm,Bolt Hole No.:4,Thread:M16,Diam.:18mm	pc

IMPA	Name	Specification	Unit
734528	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:65mm , O.D.:185mm,Thick:20mm,P.O.D.:145mm,Bolt Hole No.:4,Thread:M16,Diam.:18mm	pc
734529	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:80mm , O.D.:200mm,Thick:22mm,P.O.D.:160mm,Bolt Hole No.:8,Thread:M16,Diam.:18mm	pc
734530	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:100mm , O.D.:220mm,Thick:24mm,P.O.D.:180mm,Bolt Hole No.:8,Thread:M16,Diam.:18mm	pc
734531	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:125mm , O.D.:250mm,Thick:26mm,P.O.D.:210mm,Bolt Hole No.:8,Thread:M16,Diam.:18mm	pc
734532	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:150mm , O.D.:285mm,Thick:26mm,P.O.D.:240mm,Bolt Hole No.:8,Thread:M20,Diam.:22mm	pc
734533	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:175mm , O.D.:315mm,Thick:28mm,P.O.D.:240mm,Bolt Hole No.:8,Thread:M20,Diam.:22mm	pc
734534	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:200mm , O.D.:340mm,Thick:26mm,P.O.D.:295mm,Bolt Hole No.:8,Thread:M20,Diam.:22mm	pc
734536	DIN2532-Cast Iron Flange(10kgf/cm2)	Diam.:300mm , O.D.:445mm,Thick:28mm,P.O.D.:400mm,Bolt Hole No.:12,Thread:M20,Diam.:22mm	pc