

Jinbo Marine

Marine Stores & Equipment Datasheet

IMPA DATASHEET

73 - PIPE & TUBE FITTINGS

Anti-Corrosive Coated Flexible Pipe Coupling (For

IMPA CODE

735048

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

Key Product Information

IMPA	735048	Product Name	Anti-Corrosive Coated Flexible Pipe Coupling (For
Specification	Pipe O.D.:114.3mm,Pipe O.D.:4.5",H in:192mm,No. Of Bolts:3,Working Pres.:36 Bar,Weight:3.9kgs	Unit	pc
Category	73 - Pipe & Tube Fittings	Origin	China

Description

These expansion joints are designed to absorb quick expansion and contraction of pipes resulting from the high temperature of fluids such as exhaust gas,high-temperature water,etc.A variety of packing materials can be used based upon the temperature and t

Related IMPA Products

IMPA	Name	Specification	Unit
735041	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:57mm,Pipe O.D.:2.25",H in:135mm,No. Of Bolts:2,Working Pres.:44 Bar,Weight:2.0kgs	pc
735042	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:60.3mm,Pipe O.D.:2.375",H in:138mm,No. Of Bolts:2,Working Pres.:42 Bar,Weight:2.1kgs	pc
735043	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:70.0mm,Pipe O.D.:2.75",H in:148mm,No. Of Bolts:2,Working Pres.:37 Bar,Weight:2.7kgs	pc
735044	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:76.1mm,Pipe O.D.:3.0",H in:154mm,No. Of Bolts:2,Working Pres.:35 Bar,Weight:2.9kgs	pc
735045	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:82.5mm,Pipe O.D.:3.25",H in:167mm,No. Of Bolts:2,Working Pres.:32 Bar,Weight:3.4kgs	pc

IMPA	Name	Specification	Unit
7350 46	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:101.6mm, Pipe O.D.:4.0", H in:179mm, No. Of Bolts:3, Working Pres.:40 Bar, Weight:3.6kgs	pc
7350 47	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:108mm, Pipe O.D.:4.25", H in:186mm, No. Of Bolts:3, Working Pres.:38 Bar, Weight:3.8kgs	pc
7350 49	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:133mm, Pipe O.D.:5.25", H in:216mm, No. Of Bolts:4, Working Pres.:42 Bar, Weight:5.1kgs	pc
7350 50	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:139.7mm, Pipe O.D.:5.5", H in:222mm, No. Of Bolts:4, Working Pres.:40 Bar, Weight:5.3kgs	pc
7350 51	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:159mm, Pipe O.D.:6.25", H in:254mm, No. Of Bolts:4, Working Pres.:34 Bar, Weight:7.9kgs	pc
7350 52	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:165.1mm, Pipe O.D.:6.5", H in:260mm, No. Of Bolts:4, Working Pres.:33 Bar, Weight:8.5kgs	pc
7350 53	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:168.3mm, Pipe O.D.:6.625", H in:264mm, No. Of Bolts:4, Working Pres.:32 Bar, Weight:8.5kgs	pc
7350 54	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:168.3mm, Pipe O.D.:6.625", H in:264mm, No. Of Bolts:4, Working Pres.:32 Bar, Weight:8.5kgs	pc
7350 55	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:193.7mm, Pipe O.D.:7.625", H in:290mm, No. Of Bolts:4, Working Pres.:28 Bar, Weight:10.1kgs	pc
7350 56	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:219.1mm, Pipe O.D.:8.625", H in:315mm, No. Of Bolts:5, Working Pres.:31 Bar, Weight:11.2kgs	pc
7350 57	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:244.5mm, Pipe O.D.:9.625", H in:341mm, No. Of Bolts:5, Working Pres.:34 Bar, Weight:12.6kgs	pc
7350 59	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:323.9mm, Pipe O.D.:12.75", H in:420mm, No. Of Bolts:6, Working Pres.:26 Bar, Weight:15.9kgs	pc
7350 60	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:355.6mm, Pipe O.D.:14", H in:455mm, No. Of Bolts:6, Working Pres.:29 Bar, Weight:25.6kgs	pc
7350 61	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:406.4mm, Pipe O.D.:16", H in:506mm, No. Of Bolts:8, Working Pres.:34 Bar, Weight:29.4kgs	pc
7350 62	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:457.2mm, Pipe O.D.:18", H in:557mm, No. Of Bolts:8, Working Pres.:31 Bar, Weight:32.4kgs	pc
7350 63	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:508mm, Pipe O.D.:20", H in:608mm, No. Of Bolts:10, Working Pres.:31 Bar, Weight:36.3kgs	pc
7350 64	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:558.8mm, Pipe O.D.:22", H in:658mm, No. Of Bolts:12, Working Pres.:28 Bar, Weight:40.1kgs	pc