73 - PIPE & TUBE FITTINGS

# Anti-Corrosive Coated Flexible Pipe Coupling (For

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

**IMPA CODE**
**735048**

## Key Product Information

| | | | |
|---|---|---|---|
| **IMPA** | 735048 | **Product Name** | Anti-Corrosive Coated Flexible Pipe Coupling (For |
| **Specification** | Pipe O.D.:114.3mm,Pipe O.D.:4.5″,H in:192mm,No. Of Bolts:3,Working Pres.:36 Bar,Weight:3.9kgs | **Unit** | pc |
| **Category** | 73 - Pipe & Tube Fittings | **Origin** | China |

## Description

These expansion joints are designed to absorb quick expansion and contraction of pipes resulting from the high temperature of fluids such as exhaust gas,high-temperature water,etc.A variety of packing materials can be used based upon the temperature and t

## Related IMPA Products

| IMPA | Name | Specification | Unit |
|---|---|---|---|
| 735041 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:57mm,Pipe O.D.:2.25″,H in:135mm,No. Of Bolts:2,Working Pres.:44 Bar,Weight:2.0kgs | pc |
| 735042 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:60.3mm,Pipe O.D.:2.375″,H in:138mm,No. Of Bolts:2,Working Pres.:42 Bar,Weight:2.1kgs | pc |
| 735043 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:70.0mm,Pipe O.D.:2.75″,H in:148mm,No. Of Bolts:2,Working Pres.:37 Bar,Weight:2.7kgs | pc |
| 735044 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:76.1mm,Pipe O.D.:3.0″,H in:154mm,No. Of Bolts:2,Working Pres.:35 Bar,Weight:2.9kgs | pc |
| 735045 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:82.5mm,Pipe O.D.:3.25″,H in:167mm,No. Of Bolts:2,Working Pres.:32 Bar,Weight:3.4kgs | pc |

| IMPA | Name | Specification | Unit |
|---|---|---|---|
| 735046 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:101.6mm,Pipe O.D.:4.0″,H in:179mm,No. Of Bolts:3,Working Pres.:40 Bar,Weight:3.6kgs | pc |
| 735047 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:108mm,Pipe O.D.:4.25″,H in:186mm,No. Of Bolts:3,Working Pres.:38 Bar,Weight:3.8kgs | pc |
| 735049 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:133mm,Pipe O.D.:5.25″,H in:216mm,No. Of Bolts:4,Working Pres.:42 Bar,Weight:5.1kgs | pc |
| 735050 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:139.7mm,Pipe O.D.:5.5″,H in:222mm,No. Of Bolts:4,Working Pres.:40 Bar,Weight:5.3kgs | pc |
| 735051 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:159mm,Pipe O.D.:6.25″,H in:2542mm,No. Of Bolts:4,Working Pres.:34 Bar,Weight:7.9kgs | pc |
| 735052 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:165.1mm,Pipe O.D.:6.5″,H in:260mm,No. Of Bolts:4,Working Pres.:33 Bar,Weight:8.5kgs | pc |
| 735053 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:168.3mm,Pipe O.D.:6.625″,H in:264mm,No. Of Bolts:4,Working Pres.:32 Bar,Weight:8.5kgs | pc |
| 735054 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:168.3mm,Pipe O.D.:6.625″,H in:264mm,No. Of Bolts:4,Working Pres.:32 Bar,Weight:8.5kgs | pc |
| 735055 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:193.7mm,Pipe O.D.:7.625″,H in:290mm,No. Of Bolts:4,Working Pres.:28 Bar,Weight:10.1kgs | pc |
| 735056 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:219.1mm,Pipe O.D.:8.625″,H in:315mm,No. Of Bolts:5,Working Pres.:31 Bar,Weight:11.2kgs | pc |
| 735057 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:244.5mm,Pipe O.D.:9.625″,H in:341mm,No. Of Bolts:5,Working Pres.:34 Bar,Weight:12.6kgs | pc |
| 735059 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:323.9mm,Pipe O.D.:12.75″,H in:420mm,No. Of Bolts:6,Working Pres.:26 Bar,Weight:15.9kgs | pc |
| 735060 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:355.6mm,Pipe O.D.:14″,H in:455mm,No. Of Bolts:6,Working Pres.:29 Bar,Weight:25.6kgs | pc |
| 735061 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:406.4mm,Pipe O.D.:16″,H in:506mm,No. Of Bolts:8,Working Pres.:34 Bar,Weight:29.4kgs | pc |
| 735062 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:457.2mm,Pipe O.D.:18″,H in:557mm,No. Of Bolts:8,Working Pres.:31 Bar,Weight:32.4kgs | pc |
| 735063 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:508mm,Pipe O.D.:20″,H in:608mm,No. Of Bolts:10,Working Pres.:31 Bar,Weight:36.3kgs | pc |
| 735064 | Anti-Corrosive Coated Flexible Pipe Coupling (For | Pipe O.D.:558.8mm,Pipe O.D.:22″,H in:658mm,No. Of Bolts:12,Working Pres.:28 Bar,Weight:40.1kgs | pc |