73 - PIPE & TUBE FITTINGS

Anti-Corrosive Coated Flexible Pipe Coupling (For

Jinbo Marine supplies IMPA marine stores and ship equipment for global marine and offshore customers.

IMPA CODE
735061

Key Product Information

IMPA	735061	**Product Name**	Anti-Corrosive Coated Flexible Pipe Coupling (For
Specification	Pipe O.D.:406.4mm,Pipe O.D.:16″,H in:506mm,No. Of Bolts:8,Working Pres.:34 Bar,Weight:29.4kgs	**Unit**	pc
Category	73 - Pipe & Tube Fittings	**Origin**	China

Description

These expansion joints are designed to absorb quick expansion and contraction of pipes resulting from the high temperature of fluids such as exhaust gas,high-temperature water,etc.A variety of packing materials can be used based upon the temperature and t

Related IMPA Products

IMPA	Name	Specification	Unit
735041	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:57mm,Pipe O.D.:2.25″,H in:135mm,No. Of Bolts:2,Working Pres.:44 Bar,Weight:2.0kgs	pc
735042	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:60.3mm,Pipe O.D.:2.375″,H in:138mm,No. Of Bolts:2,Working Pres.:42 Bar,Weight:2.1kgs	pc
735043	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:70.0mm,Pipe O.D.:2.75″,H in:148mm,No. Of Bolts:2,Working Pres.:37 Bar,Weight:2.7kgs	pc
735044	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:76.1mm,Pipe O.D.:3.0″,H in:154mm,No. Of Bolts:2,Working Pres.:35 Bar,Weight:2.9kgs	pc
735045	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:82.5mm,Pipe O.D.:3.25″,H in:167mm,No. Of Bolts:2,Working Pres.:32 Bar,Weight:3.4kgs	pc

IMPA	Name	Specification	Unit
735046	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:101.6mm,Pipe O.D.:4.0″,H in:179mm,No. Of Bolts:3,Working Pres.:40 Bar,Weight:3.6kgs	pc
735047	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:108mm,Pipe O.D.:4.25″,H in:186mm,No. Of Bolts:3,Working Pres.:38 Bar,Weight:3.8kgs	pc
735048	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:114.3mm,Pipe O.D.:4.5″,H in:192mm,No. Of Bolts:3,Working Pres.:36 Bar,Weight:3.9kgs	pc
735049	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:133mm,Pipe O.D.:5.25″,H in:216mm,No. Of Bolts:4,Working Pres.:42 Bar,Weight:5.1kgs	pc
735050	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:139.7mm,Pipe O.D.:5.5″,H in:222mm,No. Of Bolts:4,Working Pres.:40 Bar,Weight:5.3kgs	pc
735051	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:159mm,Pipe O.D.:6.25″,H in:2542mm,No. Of Bolts:4,Working Pres.:34 Bar,Weight:7.9kgs	pc
735052	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:165.1mm,Pipe O.D.:6.5″,H in:260mm,No. Of Bolts:4,Working Pres.:33 Bar,Weight:8.5kgs	pc
735053	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:168.3mm,Pipe O.D.:6.625″,H in:264mm,No. Of Bolts:4,Working Pres.:32 Bar,Weight:8.5kgs	pc
735054	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:168.3mm,Pipe O.D.:6.625″,H in:264mm,No. Of Bolts:4,Working Pres.:32 Bar,Weight:8.5kgs	pc
735055	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:193.7mm,Pipe O.D.:7.625″,H in:290mm,No. Of Bolts:4,Working Pres.:28 Bar,Weight:10.1kgs	pc
735056	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:219.1mm,Pipe O.D.:8.625″,H in:315mm,No. Of Bolts:5,Working Pres.:31 Bar,Weight:11.2kgs	pc
735057	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:244.5mm,Pipe O.D.:9.625″,H in:341mm,No. Of Bolts:5,Working Pres.:34 Bar,Weight:12.6kgs	pc
735059	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:323.9mm,Pipe O.D.:12.75″,H in:420mm,No. Of Bolts:6,Working Pres.:26 Bar,Weight:15.9kgs	pc
735060	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:355.6mm,Pipe O.D.:14″,H in:455mm,No. Of Bolts:6,Working Pres.:29 Bar,Weight:25.6kgs	pc
735062	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:457.2mm,Pipe O.D.:18″,H in:557mm,No. Of Bolts:8,Working Pres.:31 Bar,Weight:32.4kgs	pc
735063	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:508mm,Pipe O.D.:20″,H in:608mm,No. Of Bolts:10,Working Pres.:31 Bar,Weight:36.3kgs	pc
735064	Anti-Corrosive Coated Flexible Pipe Coupling (For	Pipe O.D.:558.8mm,Pipe O.D.:22″,H in:658mm,No. Of Bolts:12,Working Pres.:28 Bar,Weight:40.1kgs	pc