

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

BILGE PUMP

01 Series 1100GPH Bilge Pump

01 Series 1100GPH Bilge Pump SEAFLO non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our com...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G1100-01 1100 GPH 12 V 3.0 A 5.0 A 12' (4m) 3' (1m) 1-1/8" 0.38/0....
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Bilge Pump	Model / SKU	01-Series-1100GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G1100-01 1100 GPH 12 V 3.0 A 5.0 A 12' (4m) 3' (1m) 1-1/8" 0.38/0.44 kg SFBP2-G1100-01 1100 GPH 24 V 1.8 A 3.0 A 12' (4m) 3' (1m) 1-1/8" 0.38/0.44 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 1.8 960 3634 0 12 3.1 788 2983 0.5 12 2.1 810 3066 1 12 3.2 636 2407 1.5 12 2.5 500 1893 2 12 2.9 360 1363 2.5 12 2.8 228 863 3 Voltage(V) Current(A) Flow Head(M) GPH LPH 13.6 2.1 1080 4088 0 13.6 2.4 930 3520 1 13.6 3 620 2347 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China 01 Series 1100GPH Bilge Pump:	■ STANDARD PUMP CONFIGURATIONS
	■ PERFORMANCE	

China 01 Series 1100GPH Bilge Pump:

01 Series 1100GPH Bilge Pump



SEAFL0 non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our competitors. Our removable strainer base fits industry standard mounting conventions though, so you'll have no problem changing to us from them.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G1100-01	1100 GPH	12 V	3.0 A	5.0 A	12' (4m)	3' (1m)	1-1/8"	0.38/0.44 kg
SFBP2-G1100-01	1100 GPH	24 V	1.8 A	3.0 A	12' (4m)	3' (1m)	1-1/8"	0.38/0.44 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	1.8	960	3634	0
12	3.1	788	2983	0.5
12	2.1	810	3066	1
12	3.2	636	2407	1.5
12	2.5	500	1893	2
12	2.9	360	1363	2.5
12	2.8	228	863	3

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
13.6	2.1	1080	4088	0
13.6	2.4	930	3520	1
13.6	3	620	2347	2