

**BILGE PUMP**

## 01 Series 1500GPH Bilge Pump

01 Series 1500GPH Bilge Pump SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes cl...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

<b>Category</b>	Bilge Pump
<b>Standard</b>	EN
<b>Weight / Size</b>	SFBP1-G1500-01 1500 GPH 12V 8.0 A 12.0 A 16' (5m) 3' (1m) 1-1/8" 1.13/1....
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Bilge Pump	<b>Model / SKU</b>	01-Series-1500GPH-Bilge-Pump
<b>Standard</b>	EN	<b>Weight / Size</b>	SFBP1-G1500-01 1500 GPH 12V 8.0 A 12.0 A 16' (5m) 3' (1m) 1-1/8" 1.13/1.21 kg SFBP2-G1500-01 1500 GPH 24V 4.0 A 7.0 A 16' (5m) 3' (1m) 1-1/8" 1.13/1.21 kg <b>PERFORMANCE</b> Voltage(V) Current(A) Flow Head(M) GPH LPH 12 7.1 1308 4950 0 12 5.6 976 3694 0.5 12 8 865 3274 1 12 5.8 688 2604 1.5 12 9 840 3179 2 12 6.1 596 2256 2.5 12 6.2 570 2157 3 12 6.3 538 2036 3.5 Voltage(V) Current(A) Flow Head(M) GPH LPH 13.6 8.1 1427 5401 0 13.6 8.2 963 3645 1 13.6 9 906 3429 2
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ 01 Series 1500GPH Bilge Pump</li> <li>■ STANDARD PUMP CONFIGURATIONS</li> <li>■ PERFORMANCE</li> </ul>
-----------------	---

## 01 Series 1500GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris.

## STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G1500-01	1500 GPH	12V	8.0 A	12.0 A	16' (5m)	3' (1m)	1-1/8"	1.13/1.21 kg
SFBP2-G1500-01	1500 GPH	24V	4.0 A	7.0 A	16' (5m)	3' (1m)	1-1/8"	1.13/1.21 kg

## PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	7.1	1308	4950	0
12	5.6	976	3694	0.5
12	8	865	3274	1
12	5.8	688	2604	1.5
12	9	840	3179	2
12	6.1	596	2256	2.5
12	6.2	570	2157	3
12	6.3	538	2036	3.5

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
13.6	8.1	1427	5401	0
13.6	8.2	963	3645	1
13.6	9	906	3429	2