


BILGE PUMP

01 Series 3000GPH Bilge Pump

01 Series 3000GPH Bilge Pump SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes cl...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G3000-01 3000 GPH 12 V 14.0 A 20.0 A 26' (8m) 3' (1m) 1-1/2" 2.10/...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Bilge Pump	Model / SKU	01-Series-3000GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G3000-01 3000 GPH 12 V 14.0 A 20.0 A 26' (8m) 3' (1m) 1- 1/2" 2.10/2.37 kg SFBP2-G3000- 01 3000 GPH 24 V 7.0 A 12.0 A 26' (8m) 3' (1m) 1-1/2" 2.10/2.37 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 10 2580 9765 0 12 10.2 2420 9160 0.5 12 10.5 2350 8895 1 12 10.7 2120 8024 1.5 12 11 2070 7835 2 12 11.2 1780 6737 2.5 12 11.5 1630 6170 3
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 01 Series 3000GPH Bilge Pump
- PERFORMANCE

- STANDARD PUMP CONFIGURATIONS

01 Series 3000GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G3000-01	3000 GPH	12 V	14.0 A	20.0 A	26' (8m)	3' (1m)	1-1/2"	2.10/2.37 kg
SFBP2-G3000-01	3000 GPH	24 V	7.0 A	12.0 A	26' (8m)	3' (1m)	1-1/2"	2.10/2.37 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	10	2580	9765	0
12	10.2	2420	9160	0.5
12	10.5	2350	8895	1
12	10.7	2120	8024	1.5
12	11	2070	7835	2
12	11.2	1780	6737	2.5
12	11.5	1630	6170	3