


BILGE PUMP

01 Series 3500GPH Bilge Pump

01 Series 3500GPH Bilge Pump SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes cl...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G3500-01 3500 GPH 12 V 16.0 A 25.0 A 26' (8m) 3' (1m) 1-1/2" 2.10/...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Bilge Pump	Model / SKU	01-Series-3500GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G3500-01 3500 GPH 12 V 16.0 A 25.0 A 26' (8m) 3' (1m) 1-1/2" 2.10/2.37 kg SFBP2-G3500-01 3500 GPH 24 V 8.0 A 15.0 A 26' (8m) 3' (1m) 1-1/2" 2.10/2.37 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 10.3 3080 11658 0 12 10.5 2920 11052 0.5 12 10.8 2810 10636 1 12 11 2760 10447 1.5 12 11.5 2370 8970 2 12 12 2120 8024 2.5 12 12.5 2050 7759 3
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 01 Series 3500GPH Bilge Pump
- PERFORMANCE

- STANDARD PUMP CONFIGURATIONS

01 Series 3500GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G3500-01	3500 GPH	12 V	16.0 A	25.0 A	26' (8m)	3' (1m)	1-1/2"	2.10/2.37 kg
SFBP2-G3500-01	3500 GPH	24 V	8.0 A	15.0 A	26' (8m)	3' (1m)	1-1/2"	2.10/2.37 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	10.3	3080	11658	0
12	10.5	2920	11052	0.5
12	10.8	2810	10636	1
12	11	2760	10447	1.5
12	11.5	2370	8970	2
12	12	2120	8024	2.5
12	12.5	2050	7759	3