

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

BILGE PUMP

01 Series 500GPH Bilge Pump

01 Series 500GPH Bilge Pump SEAFLO non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our comp...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

| | |
|---------------|---|
| Category | Bilge Pump |
| Standard | EN |
| Weight / Size | SFBP1-G500-01 500 GPH 12 V 1.6 A 3.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications | | | |
|--------------------------|--|---------------|--|
| Category | Bilge Pump | Model / SKU | 01-Series-500GPH-Bilge-Pump |
| Standard | EN | Weight / Size | SFBP1-G500-01 500 GPH 12 V 1.6 A 3.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg SFBP2-G500-01 500 GPH 24 V 1.2 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH OPEN 1.8 482 1824 0 12 1.4 388 1469 0.25 12 1.4 363 1374 0.5 12 1.4 342 1294 0.75 12 2 285 1079 1 12 1.4 268 1014 1.25 12 1.4 245 927 1.5 12 1.4 215 814 1.75 12 2 142 537 2 Voltage(V) Current(A) Flow Head(M) GPH LPH OPEN 1.9 539 2040 0 13.6 1.9 309 1170 1 13.6 1.9 190 719 2 |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty | 12 Months unless specified otherwise |
| Origin | China | | |

| | | |
|----------|-------------------------------|--------------------------------|
| CONTENTS | ■ 01 Series 500GPH Bilge Pump | ■ STANDARD PUMP CONFIGURATIONS |
| | ■ PERFORMANCE | |

01 Series 500GPH Bilge Pump



SEAFL0 non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our competitors. Our removable strainer base fits industry standard mounting conventions though, so you'll have no problem changing to us from them.

STANDARD PUMP CONFIGURATIONS

| Model | FlowRate | Voltage | Max Draw | Fuse Amps | Head | Wire Lead | Outlet Dia | N.W. / G.W. |
|---------------|----------|---------|----------|-----------|---------|-----------|------------|--------------|
| SFBP1-G500-01 | 500 GPH | 12 V | 1.6 A | 3.0 A | 9' (3m) | 3' (1m) | 3/4" | 0.33/0.40 kg |
| SFBP2-G500-01 | 500 GPH | 24 V | 1.2 A | 2.0 A | 9' (3m) | 3' (1m) | 3/4" | 0.33/0.40 kg |

PERFORMANCE

| Voltage(V) | Current(A) | Flow | | Head(M) |
|------------|------------|------|------|---------|
| | | GPH | LPH | |
| OPEN | 1.8 | 482 | 1824 | 0 |
| 12 | 1.4 | 388 | 1469 | 0.25 |
| 12 | 1.4 | 363 | 1374 | 0.5 |
| 12 | 1.4 | 342 | 1294 | 0.75 |
| 12 | 2 | 285 | 1079 | 1 |
| 12 | 1.4 | 268 | 1014 | 1.25 |
| 12 | 1.4 | 245 | 927 | 1.5 |
| 12 | 1.4 | 215 | 814 | 1.75 |
| 12 | 2 | 142 | 537 | 2 |

| Voltage(V) | Current(A) | Flow | | Head(M) |
|------------|------------|------|------|---------|
| | | GPH | LPH | |
| OPEN | 1.9 | 539 | 2040 | 0 |
| 13.6 | 1.9 | 309 | 1170 | 1 |
| 13.6 | 1.9 | 190 | 719 | 2 |