

01 Series 2000GPH Bilge Pump

Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G2000-01 2000 GPH 12V 8.5 A 14.0 A 20' (6m) 3' (1m) 1-1/8" 1.13/1....
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
Category	Bilge Pump	Model / SKU	01-Series-2000GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G2000-01 2000 GPH 12V 8.5 A 14.0 A 20' (6m) 3' (1m) 1-1/8" 1.13/1.21 kg SFBP2-G2000-01 2000 GPH 24V 5.0 A 8.0 A 20' (6m) 3' (1m) 1-1/8" 1.13/1.21 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 9 1427 5401 0 12 8.3 1200 4542 0.5 12 10 951 3600 1 12 8.8 1060 4012 1.5 12 10.8 919 3478 2 12 9.2 940 3558 2.5 12 9.3 850 3217 3 12 9.3 790 2990 3.5 Voltage(V) Current(A) Flow Head(M) GPH LPH 13.6 4.3 1442 5458 0 13.6 4.5 967 3660 1 13.6 4.8 951 3660 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	01 Series 2000GPH Bilge Pump - PERFORMANCE	STANDARD PUMP CONFIGURATIONS
----------	---	--

01 Series 2000GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G2000-01	2000 GPH	12V	8.5 A	14.0 A	20' (6m)	3' (1m)	1-1/8"	1.13/1.21 kg
SFBP2-G2000-01	2000 GPH	24V	5.0 A	8.0 A	20' (6m)	3' (1m)	1-1/8"	1.13/1.21 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	9	1427	5401	0
12	8.3	1200	4542	0.5
12	10	951	3600	1
12	8.8	1060	4012	1.5
12	10.8	919	3478	2
12	9.2	940	3558	2.5
12	9.3	850	3217	3
12	9.3	790	2990	3.5

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
13.6	4.3	1442	5458	0
13.6	4.5	967	3660	1
13.6	4.8	951	3660	2