

BILGE PUMP

01 Series 500GPH Bilge Pump

01 Series 500GPH Bilge Pump SEAFLO non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our comp...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G500-01 500 GPH 12 V 1.6 A 3.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Bilge Pump	Model / SKU	01-Series-500GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G500-01 500 GPH 12 V 1.6 A 3.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg SFBP2-G500-01 500 GPH 24 V 1.2 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.33/0.40 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH OPEN 1.8 482 1824 0 12 1.4 388 1469 0.25 12 1.4 363 1374 0.5 12 1.4 342 1294 0.75 12 2 285 1079 1 12 1.4 268 1014 1.25 12 1.4 245 927 1.5 12 1.4 215 814 1.75 12 2 142 537 2 Voltage(V) Current(A) Flow Head(M) GPH LPH OPEN 1.9 539 2040 0 13.6 1.9 309 1170 1 13.6 1.9 190 719 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	01 Series 500GPH Bilge Pump PERFORMANCE	STANDARD PUMP CONFIGURATIONS
----------	--	------------------------------

01 Series 500GPH Bilge Pump



SEAFL0 non-automatic bilge pumps offer water evacuation activated by a panel or float switch. Our larger impeller design and more robust motor allow us to outperform our competitors. Our removable strainer base fits industry standard mounting conventions though, so you'll have no problem changing to us from them.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G500-01	500 GPH	12 V	1.6 A	3.0 A	9' (3m)	3' (1m)	3/4"	0.33/0.40 kg
SFBP2-G500-01	500 GPH	24 V	1.2 A	2.0 A	9' (3m)	3' (1m)	3/4"	0.33/0.40 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
OPEN	1.8	482	1824	0
12	1.4	388	1469	0.25
12	1.4	363	1374	0.5
12	1.4	342	1294	0.75
12	2	285	1079	1
12	1.4	268	1014	1.25
12	1.4	245	927	1.5
12	1.4	215	814	1.75
12	2	142	537	2

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
OPEN	1.9	539	2040	0
13.6	1.9	309	1170	1
13.6	1.9	190	719	2