

BILGE PUMP

02 Series 350GPH Bilge Pump

02 Series 350GPH Bilge Pump Like our 01-series, this pump is normally activated by a panel or float switch. However, this custom strainer allows the pump to be mounted to a bulkhead or transom =, as wel...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G350-02 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.33 kg...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	02-Series-350GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G350-02 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.33 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 1.2 320 1211 0 12 1.2 295 1117 0.25 12 1.2 280 1060 0.50 12 1.3 270 1022 0.75 12 1.3 255 965 1.00 12 1.5 210 795 1.25 12 1.5 160 606 1.50
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 02 Series 350GPH Bilge Pump
- STANDARD PUMP CONFIGURATIONS
- PERFORMANCE

02 Series 350GPH Bilge Pump



Like our 01-series, this pump is normally activated by a panel or float switch. However, this custom strainer allows the pump to be mounted to a bulkhead or transom =, as well as normal bilge mounting. One type offers a barbed output, while the other is threaded in order to be flexible to your specific application.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G350-02	350 GPH	12 V	1.0 A	2.0 A	9' (3m)	3' (1m)	3/4"	0.22/0.33 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	1.2	320	1211	0
12	1.2	295	1117	0.25
12	1.2	280	1060	0.50
12	1.3	270	1022	0.75
12	1.3	255	965	1.00
12	1.5	210	795	1.25
12	1.5	160	606	1.50