

BILGE PUMP

02 Series 600GPH Bilge Pump

02 Series 600GPH Bilge Pump Like our 01-series, this pump is normally activated by a panel or float switch. However, this custom strainer allows the pump to be mounted to a bulkhead or transom =, as wel...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G600-02 600 GPH 1 2V 2.5 A 4.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.33 kg...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	02-Series-600GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G600-02 600 GPH 1 2V 2.5 A 4.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.33 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 1.7 516 1953 0 12 1.7 493 1866 0.4 12 1.7 462 1749 0.8 12 1.9 428 1620 1.2 12 1.9 336 1272 1.6 12 2.1 258 977 2 12 2.3 215 814 2.4
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ 02 Series 600GPH Bilge Pump	■ STANDARD PUMP CONFIGURATIONS
	■ PERFORMANCE	

02 Series 600GPH Bilge Pump



Like our 01-series, this pump is normally activated by a panel or float switch. However, this custom strainer allows the pump to be mounted to a bulkhead or transom =, as well as normal bilge mounting. One type offers a barbed output, while the other is threaded in order to be flexible to your specific application.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G600-02	600 GPH	1 2V	2.5 A	4.0 A	9' (3m)	3' (1m)	3/4"	0.22/0.33 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	1.7	516	1953	0
12	1.7	493	1866	0.4
12	1.7	462	1749	0.8
12	1.9	428	1620	1.2
12	1.9	336	1272	1.6
12	2.1	258	977	2
12	2.3	215	814	2.4