


BILGE PUMP

03 Series 350GPH Bilge Pump

03 Series 350GPH Bilge Pump Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for e...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G350-03 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.37/0.46 kg...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	03-Series-350GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G350-03 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.37/0.46 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 1.5 320 1211 0 12 1.5 305 1154 0.4 12 1.5 285 1079 0.8 12 1.6 225 852 1.2 12 1.8 180 681 1.6 12 1.8 155 587 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ 03 Series 350GPH Bilge Pump ■ PERFORMANCE 	<ul style="list-style-type: none"> ■ STANDARD PUMP CONFIGURATIONS
-----------------	--	--

03 Series 350GPH Bilge Pump



Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for easy maintenance. The standard connection is threaded but included are adaptors to barbed in order to be flexible to your specific needs.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G350-03	350 GPH	12 V	1.0 A	2.0 A	9' (3m)	3' (1m)	3/4"	0.37/0.46 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	1.5	320	1211	0
12	1.5	305	1154	0.4
12	1.5	285	1079	0.8
12	1.6	225	852	1.2
12	1.8	180	681	1.6
12	1.8	155	587	2