

BILGE PUMP

03 Series 600GPH Bilge Pump

03 Series 600GPH Bilge Pump Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for e...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G600-03 600 GPH 12 V 3.0 A 5.0 A 11' (3.5m) 3' (1m) 3/4" 0.37/0.46...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	03-Series-600GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G600-03 600 GPH 12 V 3.0 A 5.0 A 11' (3.5m) 3' (1m) 3/4" 0.37/0.46 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 2.4 520 1968 0 12 2.4 500 1892 0.4 12 2.4 460 1741 0.8 12 2.5 432 1635 1.2 12 2.6 360 1363 1.6 12 2.7 270 1022 2 12 2.9 220 833 2.4
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 03 Series 600GPH Bilge Pump
- STANDARD PUMP CONFIGURATIONS
- PERFORMANCE

03 Series 600GPH Bilge Pump



Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for easy maintenance. The standard connection is threaded but included are adaptors to barbed in order to be flexible to your specific needs.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G600-03	600 GPH	12 V	3.0 A	5.0 A	11' (3.5m)	3' (1m)	3/4"	0.37/0.46 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	2.4	520	1968	0
12	2.4	500	1892	0.4
12	2.4	460	1741	0.8
12	2.5	432	1635	1.2
12	2.6	360	1363	1.6
12	2.7	270	1022	2
12	2.9	220	833	2.4