


BILGE PUMP

03 Series 800GPH Bilge Pump

03 Series 800GPH Bilge Pump Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for e...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G800-03 800 GPH 12 V 4.0 A 7.0 A 13' (4m) 3' (1m) 3/4" 0.37/0.46 k...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	03-Series-800GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G800-03 800 GPH 12 V 4.0 A 7.0 A 13' (4m) 3' (1m) 3/4" 0.37/0.46 kg PERFORMANCE Voltage(V) Current(A) Flow Head(M) GPH LPH 12 2.8 710 2687 0 12 2.8 680 2574 0.5 12 2.8 635 2403 1 12 3 570 2157 1.5 12 3.1 490 1855 2 12 3.2 310 1173 2.5
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	<ul style="list-style-type: none"> ■ 03 Series 800GPH Bilge Pump ■ PERFORMANCE 	<ul style="list-style-type: none"> ■ STANDARD PUMP CONFIGURATIONS
-----------------	--	--

03 Series 800GPH Bilge Pump



Like our 02-series, this mounting bracket allows the pump to be mounted vertically. In addition, this model allows for the utmost flexibility with a removable cartridge for easy maintenance. The standard connection is threaded but included are adaptors to barbed in order to be flexible to your specific needs.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G800-03	800 GPH	12 V	4.0 A	7.0 A	13' (4m)	3' (1m)	3/4"	0.37/0.46 kg

PERFORMANCE

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	2.8	710	2687	0
12	2.8	680	2574	0.5
12	2.8	635	2403	1
12	3	570	2157	1.5
12	3.1	490	1855	2
12	3.2	310	1173	2.5