

BILGE PUMP

06 Series 750GPH Bilge Pump

06 Series 750GPH Bilge Pump All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed. ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G750-06 750 GPH 12V 3.0A 5.0 A 9' (3m) 3' (1m) 3/4" 0.47/0.52 kg S...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	06-Series-750GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G750-06 750 GPH 12V 3.0A 5.0 A 9' (3m) 3' (1m) 3/4" 0.47/0.52 kg SFBP2-G750-06 750 GPH 24V 1.6A 3.0 A 9' (3m) 3' (1m) 3/4" 0.47/0.52 kg PERFORMANCE 750GPH Voltage(V) Current(A) Flow Head(M) GPH LPH 12 2.6 690 2612 0 12 2.6 680 2574 0.4 12 2.7 620 2347 0.8 12 2.7 560 2120 1.2 12 2.8 430 1628 1.6 12 2.8 370 1400 2 12 2.8 320 1211 2.4
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 06 Series 750GPH Bilge Pump
- PERFORMANCE

- STANDARD PUMP CONFIGURATIONS

06 Series 750GPH Bilge Pump



All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G750-06	750 GPH	12V	3.0A	5.0 A	9' (3m)	3' (1m)	3/4"	0.47/0.52 kg
SFBP2-G750-06	750 GPH	24V	1.6A	3.0 A	9' (3m)	3' (1m)	3/4"	0.47/0.52 kg

PERFORMANCE

750GPH

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	2.6	690	2612	0
12	2.6	680	2574	0.4
12	2.7	620	2347	0.8
12	2.7	560	2120	1.2
12	2.8	430	1628	1.6
12	2.8	370	1400	2
12	2.8	320	1211	2.4