

BILGE PUMP

06 Series 600GPH Bilge Pump

06 Series 600GPH Bilge Pump All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed.
STAND...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G600-06 600 GPH 12V 2.5 A 4.0 A 8.2' (2.5m) 3' (1m) 3/4" 0.47/0.52...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	06-Series-600GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G600-06 600 GPH 12V 2.5 A 4.0 A 8.2' (2.5m) 3' (1m) 3/4" 0.47/0.52 kg SFBP2-G600-06 600 GPH 24V 1.5 A 3.0 A 8.2' (2.5m) 3' (1m) 3/4" 0.47/0.52 kg PERFORMANCE 600GPH Voltage(V) Current(A) Flow Head(M) GPH LPH 12 2.1 510 1930 0 12 2.1 485 1836 0.4 12 2.1 435 1646 0.8 12 2.2 375 1419 1.2 12 2.2 260 984 1.6 12 2.2 225 852 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 06 Series 600GPH Bilge Pump
- PERFORMANCE

■ STANDARD PUMP CONFIGURATIONS

06 Series 600GPH Bilge Pump



All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G600-06	600 GPH	12V	2.5 A	4.0 A	8.2' (2.5m)	3' (1m)	3/4"	0.47/0.52 kg
SFBP2-G600-06	600 GPH	24V	1.5 A	3.0 A	8.2' (2.5m)	3' (1m)	3/4"	0.47/0.52 kg

PERFORMANCE

600GPH

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	2.1	510	1930	0
12	2.1	485	1836	0.4
12	2.1	435	1646	0.8
12	2.2	375	1419	1.2
12	2.2	260	984	1.6
12	2.2	225	852	2