

BILGE PUMP

07 Series 600GPH Bilge Pump

07 Series 600GPH Bilge Pump All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed. SEAFLO shower sump pump s...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G600-07 600 GPH 12V 2.5 A 4.0 A 8.2' (2.5m) 3' (1m) 3/4" 1.17/1.35...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Bilge Pump	Model / SKU	07-Series-600GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G600-07 600 GPH 12V 2.5 A 4.0 A 8.2' (2.5m) 3' (1m) 3/4" 1.17/1.35 kg SFBP2-G600-07 600 GPH 24V 1.5 A 3.0 A 8.2' (2.5m) 3' (1m) 3/4" 1.17/1.36 kg PERFORMANCE 600GPH Voltage(V) Current(A) Flow Head(M) GPH LPH 12 2.1 510 1930 0 12 2.1 485 1836 0.4 12 2.1 435 1646 0.8 12 2.2 375 1419 1.2 12 2.2 260 984 1.6 12 2.2 225 812 2
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 07 Series 600GPH Bilge Pump
- PERFORMANCE

STANDARD PUMP CONFIGURATIONS

07 Series 600GPH Bilge Pump



All-in-one pump & float switch. No additional float switch required. Pump turns on when water level rises & shuts off when water is removed. SEAFLO shower sump pump system with multiple inlet ports for versatile usage. Clear screw-down cover and removable mesh filter for easy replacement or in the event that the pump becomes clogged with debris. Check valve on outlet prevent water back flow.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G600-07	600 GPH	12V	2.5 A	4.0 A	8.2' (2.5m)	3' (1m)	3/4"	1.17/1.35 kg
SFBP2-G600-07	600 GPH	24V	1.5 A	3.0 A	8.2' (2.5m)	3' (1m)	3/4"	1.17/1.36 kg

PERFORMANCE

600GPH

Voltage(V)	Current(A)	Flow		Head(M)
		GPH	LPH	
12	2.1	510	1930	0
12	2.1	485	1836	0.4
12	2.1	435	1646	0.8
12	2.2	375	1419	1.2
12	2.2	260	984	1.6
12	2.2	225	812	2