

**BILGE PUMP**

# 08 Series 350GPH Bilge Pump

08 Series 350GPH Bilge Pump SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Strainer allows the pump to be mounted in 2 ways, either traditionally to the bot...

- ISO9001 Supplier
- Class Certificate
- Export Supply



### Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G350-08 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.28 kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

## Technical Specifications

<b>Category</b>	Bilge Pump	<b>Model / SKU</b>	08-Series-350GPH-Bilge-Pump
<b>Standard</b>	EN	<b>Weight / Size</b>	SFBP1-G350-08 350 GPH 12 V 1.0 A 2.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.28 kg
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ 08 Series 350GPH Bilge Pump</li> </ul>	<ul style="list-style-type: none"> <li>■ STANDARD PUMP CONFIGURATIONS</li> </ul>
-----------------	---	--

## 08 Series 350GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Strainer allows the pump to be mounted in 2 ways, either traditionally to the bottom, or mounted to the side vertically. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris.

### STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G350-08	350 GPH	12 V	1.0 A	2.0 A	9' (3m)	3' (1m)	3/4"	0.22/0.28 kg