

BILGE PUMP

08 Series 600GPH Bilge Pump

08 Series 600GPH Bilge Pump SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Strainer allows the pump to be mounted in 2 ways, either traditionally to the bot...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Bilge Pump
Standard	EN
Weight / Size	SFBP1-G600-08 600 GPH 12 V 3.0 A 5.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.28 kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Bilge Pump	Model / SKU	08-Series-600GPH-Bilge-Pump
Standard	EN	Weight / Size	SFBP1-G600-08 600 GPH 12 V 3.0 A 5.0 A 9' (3m) 3' (1m) 3/4" 0.22/0.28 kg
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ 08 Series 600GPH Bilge Pump

■ STANDARD PUMP CONFIGURATIONS

08 Series 600GPH Bilge Pump



SEAFLO non-automatic bilge pumps offer standard action activated by a panel or float switch. Strainer allows the pump to be mounted in 2 ways, either traditionally to the bottom, or mounted to the side vertically. Removable strainer for easy replacement or in the event that the pump becomes clogged with debris.

STANDARD PUMP CONFIGURATIONS

Model	FlowRate	Voltage	Max Draw	Fuse Amps	Head	Wire Lead	Outlet Dia	N.W. / G.W.
SFBP1-G600-08	600 GPH	12 V	3.0 A	5.0 A	9' (3m)	3' (1m)	3/4"	0.22/0.28 kg