MARINE HOIST

10-04/15-06/20-08/25-10/32-12 HHBB Series Hoist

ISO9001 Supplier

Class Certificate

Export Supply

10-04/15-06/20-08/25-10/32-12 HHBB Series Hoist Technical Parameters: Type Capacity(Ton) Lifting Height (m) Lif...



Key Highlights


Category	Marine Hoist
Standard	EN
Weight / Size	Type Capacity(Ton) Lifting Height (m) Lifting Speed (m/min) Lifting Mote...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Hoist	**Model / SKU**	10-04-15-06-20-08-25-10-32-12-HHBB-Series-Hoist
Standard	EN	**Weight / Size**	Type Capacity(Ton) Lifting Height (m) Lifting Speed (m/min) Lifting Moter Traveing speed(m/min) Operating Moter Power(kw) Rotation speed(r/min) Phases voltage(v) Frequency(Hz) Power(kw) Rotation speed(r/min) Phases voltage(v) Frequency(Hz) HHBB10 - 04 10 3/9 2.8 3x2 1440 3 220-440 50/60 10/20 0.75x2 1440 3 220-440 50/60 HHBB15 - 06 15 3/9 1.8 3x2 1440 3 220-440 50/60 10/20 0.75x2 1440 3 220-440 50/60 HHBB20 - 08 20 3/9 1.4 3x2 1440 3 220-440 50/60 10/20 0.75x2 1440 3 220-440 50/60 HHBB25 - 10 25 3/9 1.1 3x2 1440 3 220-440 50/60 10/20 0.75x2 1440 3 220-440 50/60 HHBB32 - 12 32 3/9 0.9 3x2 1440 3 220-440 50/60 10/20 0.75x2 1440 3 220-440 50/60 Product Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China 10-04/15-06/20-08/25-10/32-12 HHBB Series Hoist:

10-04/15-06/20-08/25-10/32-12 HHBB Series Hoist



Technical Parameters:

Type	Capacity(Ton)	Lifting Height (m)	Lifting Speed (m/min)	Lifting Moter					Traveing speed(m/min)	Operating Moter				
				Power(kw)	Rotationspeed(r/min)	Phasess	voltage(v)	Frequency(Hz)		Power(kw)	Rotationspeed(r/min)	Phasess	voltage(v)	Frequency(Hz)
HHBB10 - 04	10	3/9	2.8	3x2	1440	3	220-440	50/60	10/20	0.75x2	1440	3	220-440	50/60
HHBB15 - 06	15	3/9	1.8	3x2	1440	3	220-440	50/60	10/20	0.75x2	1440	3	220-440	50/60
HHBB20 - 08	20	3/9	1.4	3x2	1440	3	220-440	50/60	10/20	0.75x2	1440	3	220-440	50/60
HHBB25 - 10	25	3/9	1.1	3x2	1440	3	220-440	50/60	10/20	0.75x2	1440	3	220-440	50/60
HHBB32 - 12	32	3/9	0.9	3x2	1440	3	220-440	50/60	10/20	0.75x2	1440	3	220-440	50/60

Product Size:

Type	Capacity	H	A	B	D	E	F	K	L	N	I-BEAM	Chain
HHBB10 - 04	10	1200	630	315	940	256	265	Φ83	68	55	150-220	Φ11.2
HHBB15 - 06	15	1360	630	315	1120	256	265	Φ115	90	72	150-220	Φ11.2
HHBB20 - 08	20	1470	630	315	1310	256	265	Φ115	90	72	150-220	Φ11.2
HHBB25 - 10	25	1500	630	315	1500	256	265	Φ142	110	85	150-220	Φ11.2
HHBB32 - 12	32	1640	630	315	1720	256	265	Φ142	110	85	150-220	Φ11.2