MARINE AIR RECEIVER

100L Vertical Service Air Reservior

ISO9001 Supplier

Class Certificate

Export Supply

Description of A type : A vertical or inclination. Marine Low-pressure air receiver is mainly used to store compressed air, and supply start up or air whistle for main engine and auxiliary engine. A-typ...



Key Highlights

Category	Marine Air Receiver
Standard	DIN
Material	Steel
Weight / Size	Type Type remark Capacity Working Pressure Internal Diameter Height Wei...
Certificate	CCS, BV, ABS, GL，LR, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Air Receiver	**Model / SKU**	100L-Vertical-Service-Air-Reservior
Standard	DIN	**Material**	Steel
Weight / Size	Type Type remark Capacity Working Pressure Internal Diameter Height Weight Mpa mm mm kg A A0.05-1.0 m3 1 300 1050 70 A0.10-1.0 0.1 400 1270 125 A0.16-1.0 0.16 400 1750 155 A0.25-1.0 0.25 500 1760 180 A0.32-1.0 0.32 500 2170 248 A0.40-1.0 0.4 600 1865 250 A0.05-3.0 0.05 3 300 1050 100 A0.08-3.0 0.08 300 1360 120 A0.10-3.0 0.1 400 1270 165 A0.16-3.0 0.16 400 1750 215 A0.25-3.0 0.25 500 1760 295 A0.32-3.0 0.32 500 2100 345 A0.40-3.0 0.4 600 1865 410 A0.50-3.0 0.5 600 2270 450	**Certificate**	CCS, BV, ABS, GL，LR, NK
Warranty	12 Months unless specified otherwise	**Origin**	China

CONTENTS

- Description of A type :
- Technical data:

Description of A type :

A vertical or inclination.

Marine Low-pressure air receiver is mainly used to store compressed air, and supply start up or air whistle for main engine and auxiliary engine.

A-type is made up of bottle valve and steel body. Body has handhole (or manhole) foe easy wash and examination, and bottle valve set up inlet/outlet valve, safety valve , pressure gauge and pressure gauge valve, drain valve etc.

B-type is made up of steel body, shell cover, manhole for easy examination and repair set in shell cover, inlet/outlet valve, safety valve, pressure gauge and pressure gauge valve, drain valve, installation seat ect.

Notice:

The specification is according to its volume and working pressure, you can choose as CB/T493-1998. You also can give us parameter concerned, we will provide non-standard products.

Technical data:

Type	Type remark	Capacity	Working Pressure	Internal Diameter	Height	Weight
			Mpa	mm	mm	kg
A	A0.05-1.0	m3	1	300	1050	70
	A0.10-1.0	0.1		400	1270	125
	A0.16-1.0	0.16		400	1750	155
	A0.25-1.0	0.25		500	1760	180
	A0.32-1.0	0.32		500	2170	248
	A0.40-1.0	0.4		600	1865	250
	A0.05-3.0	0.05	3	300	1050	100
	A0.08-3.0	0.08		300	1360	120
	A0.10-3.0	0.1		400	1270	165
	A0.16-3.0	0.16		400	1750	215
	A0.25-3.0	0.25		500	1760	295
	A0.32-3.0	0.32		500	2100	345
	A0.40-3.0	0.4		600	1865	410
	A0.50-3.0	0.5		600	2270	450