

CHAFE CHAIN

12 Inch GMPHOM 2009 HDG Pick-Up Chain

ISO9001 Supplier

Class Certificate

Export Supply

Pick-Up Chain is used for picking up a hose string and connected to a lifting lug on tanker rail hose flange. Material: Flash butt welded anchor chain Finish: Hot Dip Galvanized. Pick-Up Chain Size and ...



Key Highlights

Category	Chafe Chain
Standard	EN
Material	CM690
Weight / Size	Pick-Up Chain Size and Photo Hose Size SWL(ton) Proof Load(Kn) Link Size...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Chafe Chain	Model / SKU	12-Inch-GMPHOM-2009-HDG-Pick-Up-Chain
Standard	EN	Material	CM690
Weight / Size	Pick-Up Chain Size and Photo Hose Size SWL(ton) Proof Load(Kn) Link Size(mm) Shackle Size(mm) Ring Size(mm) Length L(M) I/D(ins) Length(ft) Gr.2 Gr.3 d1 d2 d3 D1 d4 D2 d5 Hang Off Pick-up 6,8 &10 25 5 150 210 19 21 23 25 22 125 30 9.14 1.5 30 10.67 35 12.19 12 25 8 201 281 22 24 26 28 25 125 36 9.14 1.5 30 10.67 35 12.19 16 25 11 278 389 26 28 32 35 32 135 42 9.14 1.5 30 10.67 35 12.19 20 25 15.5 367 514 30 33 36 42 38 135 46 9.14 1.5 30 10.67 35 12.19	Surface	Hot Dip Galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China 12 Inch GMPHOM 2009 HDG Pick-Up Chain:	■ Pick-Up Chain Size and Photo
----------	--	--------------------------------

China 12 Inch GMPHOM 2009 HDG Pick-Up Chain:

Pick-Up Chain is used for picking up a hose string and connected to a lifting lug on tanker rail hose flange.

Material: Flash butt welded anchor chain

Finish: Hot Dip Galvanized.

Pick-Up Chain Size and Photo



Hose Size		SWL(ton)	Proof Load(Kn)	Link Size(mm)			Shackle Size(mm)		Ring Size(mm)		Length L(M)		
I/D(ins)	Length(ft)	Gr.2	Gr.3	d1	d 2	d 3	D1	d4	D2	d5	Hang Off	Pick-up	
6,8 &10	25	5	150	210	19	21	23	25	22	125	30	9.14	1.5
	30											10.67	
	35											12.19	
12	25	8	201	281	22	24	26	28	25	125	36	9.14	1.5
	30											10.67	
	35											12.19	
16	25	11	278	389	26	28	32	35	32	135	42	9.14	1.5
	30											10.67	
	35											12.19	
20	25	15.5	367	514	30	33	36	42	38	135	46	9.14	1.5
	30											10.67	
	35											12.19	