

CHAFE CHAIN

16inch HDG Hang-off chain

Hang-off chain, also called snubbing chain is used to hang a tanker rail hose at a tanker. Safety working load is in accordance with GMPHOM 2009 "Tanker Rail Hose/Lifting Lugs"
Material: Flash butt welded anchor ch...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chafe Chain
Standard	EN
Material	CM690
Weight / Size	Hose Size SWL(ton) Proof Load(Kn) Link Size(mm) Shackle Size(mm) Ring Si...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Chafe Chain	Model / SKU	16inch-HDG-Hang-off-chain
Standard	EN	Material	CM690
Weight / Size	Hose Size SWL(ton) Proof Load(Kn) Link Size(mm) Shackle Size(mm) Ring Size(mm) Length L(M) I/D(ins) Length(ft) Gr.2 Gr.3 d1 d2 d3 D1 d4 D2 d5 Hang Off Pick-up 6,8 &10 25 5 150 210 19 21 23 25 22 125 30 9.14 1.5 30 10.67 35 12.19 12 25 8 201 281 22 24 26 28 25 125 36 9.14 1.5 30 10.67 35 12.19 16 25 11 278 389 26 28 32 35 32 135 42 9.14 1.5 30 10.67 35 12.19 20 25 15.5 367 514 30 33 36 42 38 135 46 9.14 1.5 30 10.67 35 12.19	Surface	hot dip galvanized
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China 16inch HDG Hang-off chain:

Hang-off chain, also called snubbing chain is used to hang a tanker rail hose at a tanker. Safety working load is in accordance with GMPHOM 2009 "Tanker Rail Hose/Lifting Lugs"

Material: Flash butt welded anchor chain, hot dip galvanized, others fitting: steel, hot dip galvanized.

Hose Size		SWL(ton)	Proof Load(Kn)	Link Size(mm)			Shackle Size(mm)		Ring Size(mm)		Length L(M)		
I/D(ins)	Length(ft)	Gr.2	Gr.3	d1	d 2	d 3	D1	d4	D2	d5	Hang Off	Pick-up	
6,8 &10	25	5	150	210	19	21	23	25	22	125	30	9.14	1.5
	30											10.67	
	35											12.19	
12	25	8	201	281	22	24	26	28	25	125	36	9.14	1.5
	30											10.67	
	35											12.19	
16	25	11	278	389	26	28	32	35	32	135	42	9.14	1.5
	30											10.67	
	35											12.19	

20	25	15.5	367	51 4	3 0	3 3	36	42	38	135	46	9.14	1. 5
	30											10.67	
	35											12.19	