

MARINE WINDLASS

19mm LCT Windlass

19mm LCT Combined Windlass General description The LCT combined Windlass is design for the Landing Craft Tank use to anchor operation and RAM door operation, Normally will be designed symmetry installed...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	DIN
Material	Q235
Certificate	CCS , Rina , ABS, BV, GL,

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	19mm-LCT-Windlass
Standard	DIN	Material	Q235
Certificate	CCS , Rina , ABS, BV, GL,	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 19mm LCT Combined Windlass
- General description
- Specification

19mm LCT Combined Windlass

General description

The LCT combined Windlass is design for the Landing Craft Tank use to anchor operation and RAM door operation, Normally will be designed symmetry installed on port and starboard side of the LCT. Two windlass are working together to lift the RAM by hydraulic centralized control to get the two windlass synchronous. When anchoring, they operated independently. All the detail are comply with the classification standard and client's requirement.

Specification

Working chain diameter: 19mm(AM2)

Working load: 15.3kn

Overload: 23.0kn

Support load: 95kn

Nominal speed: 9m/min

Max anchoring deepth: 82.5m

Drum load: 15kn

Drum support load: 45kn

Drum speed: 12m/min

Drum capacity: D12mmx100m