

GASOLINE ENGINE DRIVEN WATER PUMP

2-4 inch Gasoline self-priming Water Pump

2-4 inch Gasoline self-priming Water Pump Parameter 2-4 inch gasoline water pump Set Model 50KB-2G 80KB-...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Gasoline engine driven water pump
Standard	GB
Weight / Size	Head lift(m) 30 30 25 25 Max.Suction head(m) 8 8 8 8 Engine Engine model...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Gasoline engine driven water pump	Model / SKU	2-4-inch-Gasoline-self-priming-Water-Pump
Standard	GB	Weight / Size	Head lift(m) 30 30 25 25 Max.Suction head(m) 8 8 8 8 Engine Engine model 170F 170F 170F 177F Engine type Single cylinder,4-stroke,air cooled gasoline engine Displacement(CC) 208 208 208 270 Max.output power(HP) 7.5 7.5 7.5 10 Rated speed(RPM) 3600 3600 3600 3600 Fuel consumption ratio(g/kw.h) <390 <390 <390 <390 starting method Recoil start Fuel tank capacity(L) 3.6 3.6 6 6 Options Electric starter N/A N/A Available Available Oil annunciator N/A N/A Available Available Pack Packing size(mm) 480x390x400 520x395x450 615x445x540 615x445x540 Net weight(Kgs) 24 27 45 47 Gross weight(Kgs) 26 29 47 49 20FT Qty 365 335 192 192
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ 2-4 inch Gasoline self-priming Water Pump	■ Parameter
----------	---	-------------

2-4 inch Gasoline self-priming Water Pump

Parameter

2-4 inch gasoline water pump					
Set	Model	50KB-2G	80KB-3G	100KB-4Ga	100KB-4Gb
	Name	Gasoline self-priming water pump			
	Inlet/Outlet diameter	50mm(2")	80mm(3")	100mm(4")	100mm(4")
	Cont. Capacity(m3/h)	33	60	80	80
	Cont. Head lift(m)	30	30	25	25
	Max.Suction head(m)	8	8	8	8

Engine	Engine model	170F	170F	170F	177F
	Engine type	Single cylinder,4-stroke,air cooled gasoline engine			
	Displacement(CC)	208	208	208	270
	Max.output power(HP)	7.5	7.5	7.5	10
	Rated speed(RPM)	3600	3600	3600	3600
	Fuel consumption ratio(g/kw.h)	<390	<390	<390	<390
	starting method	Recoil start			
	Fuel tank capacity(L)	3.6	3.6	6	6
Options	Electric starter	N/A	N/A	Available	Available
	Oil annunciator	N/A	N/A	Available	Available
Pack	Packing size(mm)	480x390x400	520x395x450	615x445x540	615x445x540
	Net weight(Kgs)	24	27	45	47
	Gross weight(Kgs)	26	29	47	49
	20FT Qty	365	335	192	192