NAVIGATION BUOY

2.4M Steel Buoy, Navigation Buoy

Specification JB2.4 Remark Beacon light power Solar cells, and 12 VDC or 6 VDC (optional) Optional Light quality ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Navigation Buoy
Standard	DIN
Material	Steel
Weight / Size	red, single or double flash flash Range 2-10Km (optional) Optional Remot...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Navigation Buoy	**Model / SKU**	2-4M-Steel-Buoy-Navigation-Buoy
Standard	DIN	**Material**	Steel
Weight / Size	red, single or double flash flash Range 2-10Km (optional) Optional Remote telemetry Remote wireless remote telemetry (with computer software installation) (optional) Optional Synchronous flash GPS signal coordination and synchronization of consistency or less 0.2 ms (optional) Optional Diameter of Buoy (m) 2.4 Material ship plate Total Height(m) 7.6 Height of Freeboard(m) 1 Height of Lamp Standing Part(m) 4.5 Max Swing Angle(°) ≤15 Swing Cycle(s) 3 ~ 5 Max Buoyancy(t) 7 Total Weight(m) 1.9 Embalmed Paint spraing, scarifical andode Anchor Chain(mm) 34 Sinker/Anchor block(t) 3 ~ 6 Depth(m) 10 ~ 50	**Certificate**	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	**Origin**	China

China 2.4M Steel Buoy, Navigation Buoy:

Specification	JB2.4	Remark
Beacon light power	Solar cells, and 12 VDC or 6 VDC (optional)	Optional
Light quality	On the left bank: green (white light), single or more flash flash The right side: red, single or double flash flash	
Range	2-10Km (optional)	Optional
Remote telemetry	Remote wireless remote telemetry (with computer software installation) (optional)	Optional
Synchronous flash	GPS signal coordination and synchronization of consistency or less 0.2 ms (optional)	Optional
Diameter of Buoy (m)	2.4	
Material	ship plate	
Total Height(m)	7.6	
Height of Freeboard(m)	1	
Height of Lamp Standing Part(m)	4.5	
Max Swing Angle(°)	≤15	

Swing Cycle(s)	3 ~ 5
Max Buoyancy(t)	7
Total Weight(m)	1.9
Embalmed	Paint spraing, scarifical andode
Anchor Chain(mm)	34
Sinker/Anchor block(t)	3 ~ 6
Depth(m)	10 ~ 50