

MARINE OIL WATER SEPERATOR

2.50m3/h Marine Oil Water Separator

2.50m3h Marine Oil Water Separator: To comply with resolution IMO MEPC.107 (49), on board, especially ocean-going ships, they must be installed on board: 15ppm bilge separator, 15ppm bilge alarm and automatic sto...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Oil Water Seperator
Standard	DIN
Weight / Size	Workgin Principle:
Certificate	CCS,GL,BV etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Oil Water Seperator	Model / SKU	2-50m3-h-Marine-Oil-Water-Separator
Standard	DIN	Weight / Size	Workgin Principle:
Certificate	CCS,GL,BV etc.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 2.50m3h Marine Oil Water Separator:
- Workgin Principle:
- Technical Data:

2.50m3h Marine Oil Water Separator:

To comply with resolution IMO MEPC.107 (49), on board, especially ocean-going ships, they must be installed on board: 15ppm bilge separator, 15ppm bilge alarm and automatic stopping device.

Workgin Principle:

the main parts adopt international famous brands, including electrical control box components provided by Schneider, 15ppm bilge alarm provided by the German DECKMA Ha, screw pump provided by the Mono Pump.

Technical Data:

Rated capacity		2.50 m3 per hour
Power of the electric heater		6kw
Power of the electric motor		1.5kw
Outline Dimension(LxWxH)		1900x1120x1900
Base		8#
Weight	Dry Weight	1500
	Wet Weight	2800
Applicable Vessel		50-100DWT
Optional electrical system		AC 380V/50Hz/3 phase,AC 415V/50Hz/3 phase, AC 440/60Hz/3 phase,AC 480V/60HZ/33 phase.
Oil content of the discharged water		Not more than 15ppm
Suction head		Not more than 6m-H2O
Pressure of the discharged water		5-10m-H2O