

MARINE AIR RECEIVER

200Litres 30bar Vertical Marine Air Receiver A0.2-3

ISO9001 Supplier

Class Certificate

Export Supply

200Litres 30barVertical Marine Air Receiver A0.2-3 Type A Vertical Marine Air Receiver is made up of bottle valve and steel body. Body has handhole(or manhole) for easy wash and examination. And bottle v...



Key Highlights

Category	Marine Air Receiver
Material	200Litres 30barVertical Marine Air Receiver A0.2-3 Type A Vertical Marin...
Weight / Size	Mpa Inner Dia mm Height mm Weight kg A A0.05-1.0 0.05 1 300 1050 70 A0.1...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Air Receiver	Model / SKU	200Litres-30bar-Vertical-Marine-Air-Receiver-A0-2-3
Material	200Litres 30barVertical Marine Air Receiver A0.2-3 Type A Vertical Marine Air Receiver is made up of bottle valve and steel body.	Weight / Size	Mpa Inner Dia mm Height mm Weight kg A A0.05-1.0 0.05 1 300 1050 70 A0.10-1.0 0.1 400 1270 125 A0.16-1.0 0.16 400 1750 155 A0.25-1.0 0.25 500 1760 180 A0.32-1.0 0.32 500 2170 248 A0.40-1.0 0.4 600 1865 260 A0.05-3.0 0.05 3 300 1050 100 A0.08-3.0 0.08 300 1360 120 A0.10-3.0 0.1 400 1270 165 A0.16-3.0 0.16 400 1750 215 A0.25-3.0 0.25 500 1760 195 A0.32-3.0 0.32 500 2100 345 A0.40-3.0 0.4 600 1865 410 A0.50-3.0 0.5 600 2270 450
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China 200Litres 30bar Vertical Marine Air Receiver A0.2-3:

200Litres 30barVertical Marine Air Receiver A0.2-3

Type A Vertical Marine Air Receiver is made up of bottle valve and steel body. Body has handhole(or manhole) for easy wash and examination.

And bottle valve set up inlet/outlet valve, safety valve, pressure gauge and pressure guage valve, drain valve, etc.

Main Specification

Style	Type	Capacity(m3)	W.P. Mpa	Inner Dia mm	Height mm	Weight kg
-------	------	--------------	----------	--------------	-----------	-----------

A	A0.05-1.0	0.05	1	300	1050	70
	A0.10-1.0	0.1		400	1270	125
	A0.16-1.0	0.16		400	1750	155
	A0.25-1.0	0.25		500	1760	180
	A0.32-1.0	0.32		500	2170	248
	A0.40-1.0	0.4		600	1865	260
	A0.05-3.0	0.05	3	300	1050	100
	A0.08-3.0	0.08		300	1360	120
	A0.10-3.0	0.1		400	1270	165
	A0.16-3.0	0.16		400	1750	215
	A0.25-3.0	0.25		500	1760	195
	A0.32-3.0	0.32		500	2100	345
	A0.40-3.0	0.4		600	1865	410
	A0.50-3.0	0.5		600	2270	450

