

MARINE WINDLASS

22mm Double Gypsy Electric Anchor Windlass

ISO9001 Supplier

Class Certificate

Export Supply

22mm Double Gypsy Electric Anchor Windlass Main Parameter Anchor Chain diameter: 22mm(AM2) Gypsy diameter: 299mm Working load: 20.6kn Overload: 30.9kn Support load: 126kn Nomin...



Key Highlights

Category	Marine Windlass
Standard	EN
Material	Q235
Weight / Size	9m/min Max anchor weight:
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	22mm-Double-Gypsy-Electric-Anchor-Windlass
Standard	EN	Material	Q235
Weight / Size	9m/min Max anchor weight:	Certificate	ABS,LR, BV, GL, CCS, RINA, IRS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ 22mm Double Gypsy Electric Anchor Windlass

■ Main Parameter

22mm Double Gypsy Electric Anchor Windlass

Main Parameter

Anchor Chain diameter: 22mm(AM2)

Gypsy diameter: 299mm

Working load: 20.6kn

Overload: 30.9kn

Support load: 126kn

Nominal speed: 9m/min

Max anchor weight: 660kg

Max anchoring deepth: 82.5m

Warping head load: 10kn

Speed: 9m/min

Working rope diameter: 30mm

Transmission ratio: 96.3

Transmission efficiency: 0.62

Motor model: JZ2-H33-4/12

Speed: 1450/500 rpm

power: 8.5/3.5kw

Voltage: 380v/50hz

Working: 30/10 min