

LIFE RAFT

25 Persons Throw-Over Board Inflatable Life Raft

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: The Throw over board Inflatable Liferaft are stored in containers on deck an inflate in the water when the painter line is pulled The standard sizes of the liferafts are available with:6、 ...



Key Highlights

Category	Life Raft
Standard	EN
Material	rubber
Weight / Size	The Throw over board Inflatable Liferaft are stored in containers on dec...
Certificate	CCS / EC

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Life Raft	Model / SKU	25-Persons-Throw-Over-Board-Inflatable-Life-Raft
Standard	EN	Material	rubber
Weight / Size	The Throw over board Inflatable Liferaft are stored in containers on deck an inflate in the water when the painter line is pulled The standard sizes of the liferafts are available with:6、 10、 15、 20 and 25 persons.	Surface	The installation height is 18-50m from water surface.
Certificate	CCS / EC	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Product Description:
- Product Parameter:
- Product Standard:
- Inflation method:
- Rules and relevant Regulations:
- Optional accessories:

Product Description:

The Throw over board Inflatable Liferaft are stored in containers on deck and inflate in the water when the painter line is pulled.

The standard sizes of the liferafts are available with: 6, 10, 15, 20 and 25 persons.

The liferafts with type approval by CCS and EC (EC was issued by GL).

Inflation method:

After throw over from ship, the liferaft can be inflated and opened automatically. If the ship sinks very fast and the life-raft can not be throw over, the raft still can float up from water under the action of Hydrostatic Release Unit and can be inflated and opened automatically.

Product Parameter:

The installation height is 18-50m from water surface.

Capacity: 25 persons

Main dimension length: 4300mm

Main dimension breadth: 4220mm

(CO₂+N₂)*2/weight of gas: 4200*2g

Max storage height: 36M

Physical form: regular sixteen-sided polygon

Gross weight: 210kg

The FRP container: Diameter 700X1460

Packaging size: 1540X780X820MM

Rules and relevant Regulations:

1996 Amendment to the International Convention for the Safety of life at Sea 1974 and MSC.48(66) The International Life-saving Appliance Code and Register of Shipping of the People's Republic of China (Technical Regulation for statutory surveys of sea-going Ships Engaged On International Voyages) 1999.

It is suitable for installing ships on international voyages.

Product Standard:

It meets the requirements of "Technical Regulations for the Statutory Surveys of Sea-going Ships Engaged on International Voyages (1999)" of P.R.C. And SOLAS 74/96 Amendment, LSA and MSC.218(82).

Equipment Outfitting

A Pack (Ships engaged on Short international voyag

Optional accessories:

Cradle,HRU (hydraulic release unit),GRP containers.