

LIFE BOAT & RESCUE BOAT

26 to 130 persons F.R.P. Totally Enclosed Lifeboat/Rescue boat

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: It is Made of fiber reinforced plastic, hull inside filled with polyurethane foams to ensure enough sufficient buoyancy of lifeboat.It fitted with self righting device.

Technical P...



Key Highlights

Category	Life boat & Rescue Boat
Standard	EN
Material	GRP
Weight / Size	Type MAIN DIM.(m) CAPACITY(p) Hook distance(m) Host power(kw) Empty boat...
Certificate	CCS, BV, DNV, ABS, GL, LR, RINA, NK

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Life boat & Rescue Boat	Model / SKU	26-to-130-persons-F-R-P-Totally-Enclosed-Lifeboat-Rescue-boat
Standard	EN	Material	GRP
Weight / Size	Type MAIN DIM.(m) CAPACITY(p) Hook distance(m) Host power(kw) Empty boat weight(kg) Full load boat weight(kg) BCC-5.0M 5.00X2.20X1.10 26 4.6 380J- 3/20.6 3JH30A/22.1 DV29/21.3 2107 4252 BCF-5.0M 5.00X2.20X1.10 26 4.6 2402 4547 BCC-5.7M 5.70X2.30X1.15 30 5.3 2273 4748 BCF-5.7M 5.70X2.30X1.15 30 5.3 2611 5086 BCC-6.5M 6.50X2.32X1.15 36 6.1 2861 5831 BCF-6.5M 6.50X2.32X1.15 36 6.1 3136 6106 BCC-7.5M 7.50X2.70X1.20 55 7 2832 7370 BCF-7.5M 7.50X2.70X1.20 55 7 3137 7675 BCC-8.0M 8.00X2.86X1.15 70 7.6 3395 9170 BCF-8.0M 8.00X2.86X1.15 70 7.6 3695 9470 BCC-8.5M 8.50X3.15X1.20 85 8.1 4360 11372.5 BCF-8.5M 8.50X3.15X1.20 85 8.1 4655 11667.5 BCC-9.5M 9.50X3.70X1.25 115 8.9 485J-3/30 DV48/35.3 5200 14687.5 BCF- 9.5M 9.50X3.70X1.25 115 8.9 5600 15087.5 BCC-10.3M 10.3X3.70X1.25 130 9.73 5618 16343 BCF-10.3M 10.3X3.70X1.25 130 9.73 6183 16908 BCC is common type,BCF is fire-resistant type	Certificate	CCS, BV, DNV, ABS, GL, LR, RINA, NK
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	Product Description:	Technical Parameter:
----------	--	--

Product Description:

It is Made of fiber reinforced plastic, hull inside filled with polyurethane foams to ensure enough sufficient buoyancy of lifeboat.It fitted with self righting device.

Technical Parameter:

Type	MAIN DIM.(m)	CAPACITY(p)	Hook distance(m)	Host power(kw)	Empty boat weight(kg)	Full load boat weight(kg)
BCC-5.0M	5.00X2.20X1.10	26	4.6	380J-3/20.6 3JH30A/22.1 DV29/21.3	2107	4252
BCF-5.0M	5.00X2.20X1.10	26	4.6		2402	4547
BCC-5.7M	5.70X2.30X1.15	30	5.3		2273	4748
BCF-5.7M	5.70X2.30X1.15	30	5.3		2611	5086
BCC-6.5M	6.50X2.32X1.15	36	6.1		2861	5831
BCF-6.5M	6.50X2.32X1.15	36	6.1		3136	6106
BCC-7.5M	7.50X2.70X1.20	55	7		2832	7370
BCF-7.5M	7.50X2.70X1.20	55	7		3137	7675
BCC-8.0M	8.00X2.86X1.15	70	7.6		3395	9170
BCF-8.0M	8.00X2.86X1.15	70	7.6		3695	9470
BCC-8.5M	8.50X3.15X1.20	85	8.1		4360	11372.5
BCF-8.5M	8.50X3.15X1.20	85	8.1		4655	11667.5
BCC-9.5M	9.50X3.70X1.25	115	8.9	485J-3/30 DV48/35.3	5200	14687.5
BCF-9.5M	9.50X3.70X1.25	115	8.9		5600	15087.5
BCC-10.3M	10.3X3.70X1.25	130	9.73		5618	16343
BCF-10.3M	10.3X3.70X1.25	130	9.73		6183	16908

BCC is common type,BCF is fire-resistant type