

MARINE WINDLASS

26mm Double Gypsy Electric Anchor Windlass

26mm Double Gypsy Electric Anchor Windlass Main specification: 1 Chain dia. (AM2) ϕ26 mm 2 Pitch dia.of the chain wheel ϕ354 mm 3 Rated pull 28.7 kN 4 Ov...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	DIN
Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Marine Windlass	Model / SKU	26mm-Double-Gypsy-Electric-Anchor-Windlass
Standard	DIN	Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 26mm Double Gypsy Electric Anchor Windlass
- Main specification: 1 Chain dia. (AM2) ϕ26 mm 2 Pitch dia.of the chain wheel ϕ354 mm 3 Rated pull 28.7 kN 4 Overload pull 43.1kN 5 Holding load 175 kN 6 Nominal speed ≥9m/min 7 Max anchor casting depth ≤82.5 m 8 Load of warping end 15 kN 9 Motor JZ2—H33—4/12 Power 8.5/3.5 kW Speed 1370/390 r/min Source 400V/ 50Hz Duty 30/10 min

26mm Double Gypsy Electric Anchor Windlass

Main specification:	1 Chain dia. (AM2) ϕ26 mm	2 Pitch dia.of the chain wheel ϕ354 mm	3 Rated pull 28.7 kN	4 Overload pull 43.1kN	5 Holding load 175 kN	6 Nominal speed ≥9m/min	7 Max anchor casting depth ≤82.5 m	8 Load of warping end 15 kN	9 Motor JZ2—H33—4/12	Power 8.5/3.5 kW	Speed 1370/390 r/min	Source 400V/ 50Hz	Duty 30/1 min
---------------------	-----------------------------	--	----------------------	------------------------	-----------------------	-------------------------	------------------------------------	-----------------------------	----------------------	------------------	----------------------	-------------------	---------------