

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

HAND PUMP

2CY-3/2.5 Marine Gear Pump

 2CY Series of gear pump is used to deliver non-corrosive lubricating oil at temperature below 80°C or equivalent liquid without solid particles and fibres and with the viscosity of 5-1500CST. ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hand Pump
Standard	EN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Hand Pump	Model / SKU	2CY-3-2-5-Marine-Gear-Pump
Standard	EN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China 2CY-3/2.5 Marine Gear Pump:

2CY Series of gear pump is used to deliver non-corrosive lubricating oil at temperature below 80°C or equivalent liquid without solid particles and fibres and with the viscosity of 5-1500CST.





Main Technical Data				
Model	Pump flow rate (L/min)	Rev speed (r/min)	Discharge pressuer (Mpa)	Motor power (KW)
2CY-1.08/2.5	18	1440	2.5	1.5
2CY-2.1/2.5	35	1440	2.5	3
2CY-3/2.5	50	1440	2.5	4
2CY-4.2/2.5	70	1440	2.5	5.5
2CY-7.5/2.5	125	1440	2.5	7.5
2CY-12/2.5	200	1460	2.5	11