MEDIUM PRESSURE AIR COOLED MARINE AIR COMPRESSOR

2ZFC-0.34/30-B Marine Emergency Air Compressor

ISO9001 Supplier

Class Certificate

Export Supply

Model: 2ZFC-0.34/30-B Marine Emergency Air Compressor Type: double row, air cooled, two stage compression piston Displacement: 0.34 m3 / min (20.4 m3 / h) The rated pressure: 3.0 MPa The air compressor host and ZFC ...



Key Highlights

Category	Medium Pressure Air Cooled Marine Air Compressor
Standard	DIN
Weight / Size	With highly efficient, light weight, small volume, low noise, smooth ope...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Medium Pressure Air Cooled Marine Air Compressor	**Model / SKU**	2ZFC-0-34-30-B-Marine-Emergency-Air-Compressor
Standard	DIN	**Weight / Size**	With highly efficient, light weight, small volume, low noise, smooth operation Products with manual/automatic stop, start, and unloading relief function.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China 2ZFC-0.34/30-B Marine Emergency Air Compressor:
- Specification
- Product features

China 2ZFC-0.34/30-B Marine Emergency Air Compressor:

Model: 2ZFC-0.34/30-B Marine Emergency Air Compressor
Type: double row, air cooled, two stage compression piston
Displacement: 0.34 m3 / min (20.4 m3 / h)
The rated pressure: 3.0 MPa
The air compressor host and ZFC - 0.34/30-2 B type Marine air compressor series products. Products with a Marine air-cooled diesel engine, with the hand to pull the centrifugal clutch starting, easy to operate. Products are especially suitable for the ship can reliable operation in emergency situations, is to ensure that the necessary for safe navigation of the ship.

Product features

Type has a single row, double row, V, W, the secondary compression piston.
With highly efficient, light weight, small volume, low noise, smooth operation
Products with manual/automatic stop, start, and unloading relief function.
Apply to ship host to start.

Specification

Model	Displacement		Specified Pressure	Rotating Speed	Motor Power		Dimension（L×W×H）	Weight
	m3/h	m3/min	MPa	r/min	kW	HP	mm	kg
2ZFC-0.34/30-B(Emergency air compressor)	20.4	0.34	3.0	600	KM186F Diesel engine		1000×500×780	170
					Diesel-engine Model KM186F		Starting method: hand drawn centrifugal clutch	