

VORTEX PUMP

3/4W0.7-10.5 Single-stage Vortex Pump

3/4W0.7-10.5 single-stage vortex pump W. WTD. single-stage vortex pump, DB two-stage vortex pump, generally conveying liquids with a temperature not exceeding 60 °C, non corrosive, solid particle free, low flow rate...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

Category	Vortex Pump
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications


Category	Vortex Pump	Model / SKU	3-4W0-7-10-5-Single-stage-Vortex-Pump
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- 3/4W0.7-10.5 single-stage vortex pump
- Technical data:

3/4W0.7-10.5 single-stage vortex pump

W. WTD. single-stage vortex pump, DB two-stage vortex pump, generally conveying liquids with a temperature not exceeding 60 °C, non corrosive, solid particle free, low flow rate, high pressure, suitable for marine, land, boiler water supply, etc.



Technical data:

Model	Flow	Head	Speed	Motor power	efficiency	Voltage	Allow suction height	Sealing form
	m ³ /h	m	r/min	kw	%	v	m	
3/4W0.7-10.5	0.7	105	2900	2.2	23	380/440	4	Asbestos filler
3/4WTD0.7-10.5	0.7	105	2900	1.5	30	380/440	5	Mechanical seal
1W2.4-10.5	2.4	105	2900	3	28	380/440	4	Asbestos filler
1WTD2.4-10.5	2.4	105	2900	2.2	30	380/440	5	Mechanical seal
1W2.5-12	2.5	120	2900	3	29	380/440	4	Asbestos filler
1WTD2.5-12	2.5	120	2900	3	30	380/440	5	Mechanical seal
1.5DB-0.7	2.4	105	2900					