

WATER TREATMENT EQUIPMENT

3 Ton/ day Marine RO Fresh Water Generator

ISO9001 Supplier

Class Certificate

Export Supply

Product Description: RO Fresh Water maker production Water meets the WHO international drinking water standards. Production water can be directly drinking.Fresh Water maker model was designed according the average ...



Key Highlights

Category	Water Treatment Equipment
Standard	DIN
Material	Stainless steel
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Water Treatment Equipment	Model / SKU	3-Ton-day-Marine-RO-Fresh-Water-Generator
Standard	DIN	Material	Stainless steel
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Product Description:
 - Parameter:
- Technical specification:

Product Description:

RO Fresh Water maker production Water meets the WHO international drinking water standards. Production water can be directly drinking.Fresh Water maker model was designed according the average seawater salinity 35000ppm.

This water maker is designed to produce drinking water from seawater.

Reverse Osmosis Fresh Water maker with a capacity of 3 t/day fresh water a/day by a seawater temperature from 10 to 27 C°. The rest salinity will be various below 700 ppm for drinking water.

Technical specification:

The water maker is specifically designed for seagoing vessels and offshore purposes. High pressure piping is made out of stainless steel AISI 316 suitable for pressure up to 100 Bar, the connection between high pressure pump and the system consist out of a flexible high pressure hose.

The low pressure piping is made out of PPR or UPVC, this material is specially suitable for ships and offshore unit due to the flexibility and strength.

Parameter:

- 1 Voltage 3-415VAC, 50Hz
- 2 Power consumption 2 kw,
- 3 Capacity: 3 ton/day
- 4 Salt content of sea water: 35000ppm
- 5 Sea water temperature: 10°C~27°C
- 6 Working condition: 10°C~45°C
- 7 Salt content of Fresh Water: ≤700ppm
- 8 Booster pump One set (loose supply , The suction under the waterline)
- 9 High pressure pump One set
- 10 Membranes Dow/ HYDRANAUTICS
- 11 Inlet of Sea water: G1" Female thread
- 12 BRINE WATER DISCHARGE G1/2" Female thread
- 13 Product water Outlet G1/2" Female thread