

ANCHOR CHAIN

32mm Grade 2 Studless Stud Link Anchor Chain

ISO9001 Supplier

Class Certificate

Export Supply

Studless Link Anchor Chain also named open link anchor chain, grade 2 or garde 3. Finish: Black Painted. The inside length (grip or pitch) of one link is 4D. The outside length of one link is 6D....



Key Highlights

Category	Anchor Chain
Standard	EN
Material	Steer Bars CM490 CM690
Weight / Size	Diameter CHAIN LINK SIZE Grade 2 Grade 3 APPROX.
Certificate	BV, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Anchor Chain	Model / SKU	32mm-Grade-2-Studless-Stud-Link-Anchor-Chain
Standard	EN	Material	Steer Bars CM490 CM690
Weight / Size	Diameter CHAIN LINK SIZE Grade 2 Grade 3 APPROX.	Surface	Painted
Certificate	BV, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China 32mm Grade 2 Studless Stud Link Anchor Chain:
- Specification:

China 32mm Grade 2 Studless Stud Link Anchor Chain:

Studless Link Anchor Chain also named open link anchor chain, grade 2 or garde 3.

Finish: Black Painted.

The inside length (grip or pitch) of one link is 4D.

The outside length of one link is 6D.

The outside width of one link is 3.56D.

The gauge-test length is the outside length over 6 links and equals 26 wire diameters.

The length of a standard "shot" = 15 fathoms = 90ft.= 1080"

Class Certifications: ABS(USA), BV(France), CCS(China), DNV(Norway), GL(Germany), KR(Korea), LR(U. K.), NK(Japan), RINA(Italy), RS(Russia) & Works Certificate.

Specification:

Diameter	CHAIN LINK SIZE		Grade 2		Grade 3		APPROX. WEIGHT
			U2 OPEN LINK CHAIN		U3 OPEN LINK CHAIN		
	OUTSIDE LENGTH	OUTSIDE WIDTH	PROOF LOAD	BREAKING LOAD	PROOF LOAD	BREAKINGLOAD	KG/27.5M
MM	MM	MM	KN	KN	KN	KN	
12.5	75	45	41.2	82.6	56.4	112.8	85.41
14	84	50.4	51	101.9	70.76	141.51	106.55
16	96	57.6	66.2	132.3	92.42	184.83	139.43
17.5	105	63	78.89	157.78	110.55	221.1	178.35
19	114	68.4	93.6	187.2	130.32	260.64	217.68
20.5	123	73.8	108.64	217.27	151.7	303.42	229.14
22	132	79.2	125.4	250.9	174.4	349.4	264.49
24	144	86.4	149.9	298.9	207.9	415.8	341.82
26	156	93.6	175.4	350.8	244	488	369.94
28	168	100.8	203.8	406.7	283	566	427.04
30	180	108	234.2	467.5	324.9	649.8	490.98
32	192	115.2	265.6	531.2	369.6	739.3	559.65
34	204	122.4	299.9	599.8	417.3	834.6	671.52
36	216	129.6	336.1	672.3	467.8	935.7	707.85
38	228	136.8	374.4	748.7	521.3	1042.5	788.98
40	240	144	414.5	829.1	577.6	1155.2	869.36
42	252	151.2	457.7	915.3	636.8	1273.6	959.3
44	264	158.4	502.7	999.6	698.9	1398	1111.25

46	276	165.6	548.8	1097.6	763.9	1527.8	1152.07
48	288	172.8	597.8	1195.6	831.7	1663.5	1256.26
50	300	180	648.8	1239.6	902.5	1805	1360.41
52	312	187.2	697.63	1395.26	976.14	1952.28	1485.61
54	324	194.4	752.33	1504.66	1052.68	2105.36	1648.08
56	336	201.6	809.09	1618.18	1132.1	2264.2	1715.97
58	348	208.8	867.91	1735.82	1214.4	2428.8	1844.5
60	360	216	928.8	1857.6	1299.6	2599.2	1973.29
62	372	223.2	991.75	1983.5	1387.68	2775.36	2101.56
64	384	230.4	1056.77	2113.54	1478.66	2957.32	2298.47
66	396	237.6	1123.85	2247.7	1572.52	3145.04	2398.1
68	408	244.8	1192.99	2385.98	1669.26	3338.52	2522.88
70	420	252	1264.2	2528.4	1768.9	3537.8	2697.65