

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

## DIAPHRAGM PUMP

# 35 Series DC Diaphragm Pump

35 Series DC Diaphragm Pump General description: 12V/24V 2.0-8.0LPM 17-160PSI The 35-Series is our continuous-duty on-demand positive displacement pump. Quick-Attach fittings allow for easy in...

ISO9001 Supplier

Class Certificate


Export Supply



### Key Highlights

Category	Diaphragm Pump
Standard	EN
Weight / Size	PUMP Type 3 Chamber positive displacement diaphragm pump, self priming, ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.



Technical Specifications			
<b>Category</b>	Diaphragm Pump	<b>Model / SKU</b>	35-Series-DC-Diaphragm-Pump
<b>Standard</b>	EN	<b>Weight / Size</b>	PUMP Type 3 Chamber positive displacement diaphragm pump, self priming, capable of being run dry Control Type Pressure switch Max Recommended Temperature 60° C ( 140° F ) Priming Capabilities 6 feet (1.8 m) suction lift Re-start Pressure Shut-off Pressure 80PSI : 65 PSI ±5 PSI(±0.3 bar) Inlet/Outlet Ports 5/8" (16mm) QUICK ATTACH Weight 5.2 lbs (2.3 kg) MOTOR Leads 16 AWG, 13" (33cm) long with 2-Pin connector/Leads Duty Cycle Continuous Max.Amp Draw 9.0 A Fuse 13.5 A STANDARD PUMP CONFIGURATIONS Model Voltage Open Flow (GPM/LPM) Control Type Max Draw Shut-off Pressure (PSI/BAR) Valves Diaphragm Ports Wire Connections SFDP1-015-080-35 12V 1.5 / 5.5 Switch 8.0 80 / 5.5 EPDM Santoprene QUICK ATTACH 2-Pin/Leads SFDP2-015-080-35 24V 1.5 / 5.5 Switch 4.5 80 / 5.5 EPDM Santoprene QUICK ATTACH 2-Pin/Leads SFDP1-018-080-35 12V 1.8 / 7.0 Switch 9.0 80 / 5.5 EPDM Santoprene QUICK ATTACH 2-Pin/Leads SFDP2-018-080-35 24V 1.8 / 7.0 Switch 4.5 80 / 5.5 EPDM Santoprene QUICK ATTACH 2-Pin/Leads
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	<b>Warranty</b>	12 Months unless specified otherwise
<b>Origin</b>	China		

<b>CONTENTS</b>	■ 35 Series DC Diaphragm Pump	■ General description:
	■ Parameter pump and motor:	■ STANDARD PUMP CONFIGURATIONS



## 35 Series DC Diaphragm Pump



### General description:

12V/24V 2.0-8.0LPM 17-160PSI

The 35-Series is our continuous-duty on-demand positive displacement pump. Quick-Attach fittings allow for easy installation or replacement. It provides reliable performance in moderate water flow, high-pressure applications. This 3-chamber diaphragm pump provides up to 1.8 gallons per minute and is capable of self-priming up to 6 vertical feet, and can run dry without damage. Miniature multi outlet water pressure pump serves 1 or 2 3/8" (10 mm) outlets at any one time. This automatic demand water system pump has a built-in pressure switch, which automatically starts and stops when the fixture is opened and closed. They are easy to install, service and winterize.

### Parameter pump and motor:

PUMP	
Type	3 Chamber positive displacement diaphragm pump, self priming, capable of being run dry
Control Type	Pressure switch
Max Recommended Temperature	60° C ( 140° F )
Priming Capabilities	6 feet (1.8 m) suction lift
Re-start Pressure	Shut-off Pressure 80PSI : 65 PSI ±5 PSI(±0.3 bar)
Inlet/Outlet Ports	5/8" (16mm) QUICK ATTACH
Weight	5.2 lbs (2.3 kg)

MOTOR	
Leads	16 AWG, 13" (33cm) long with 2-Pin connector/Leads
Duty Cycle	Continuous
Max.Amp Draw	9.0 A
Fuse	13.5 A

## STANDARD PUMP CONFIGURATIONS

Model	Voltage	Open Flow (GPM/LPM)	Control Type	Max Draw	Shut-off Pressure (PSI/BAR)	Valves	Diaphragm	Ports	Wire Connections
SFDP1-015-080-35	12V	1.5 / 5.5	Switch	8.0	80 / 5.5	EPDM	Santoprene	QUICK ATTACH	2-Pin/Leads
SFDP2-015-080-35	24V	1.5 / 5.5	Switch	4.5	80 / 5.5	EPDM	Santoprene	QUICK ATTACH	2-Pin/Leads
SFDP1-018-080-35	12V	1.8 / 7.0	Switch	9.0	80 / 5.5	EPDM	Santoprene	QUICK ATTACH	2-Pin/Leads
SFDP2-018-080-35	24V	1.8 / 7.0	Switch	4.5	80 / 5.5	EPDM	Santoprene	QUICK ATTACH	2-Pin/Leads