

MARINE FAIRLEAD

360 Degree Swivel Fairlead

Feature: 1.Excellent quality. 2.Competitive price . 3.Durable, long lifetime. Fairlead is a device to change the cable direction used for guiding ropes in ship mooring and will not breakdown. Pr...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fairlead
Standard	JIS
Material	Steel
Weight / Size	Sheave Dia.(mm) Dimension(mm) Mass Weight mm inch A B C D E F kg 19 3/4"...
Certificate	ABS , BV, mill certificate etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Fairlead	Model / SKU	360-Degree-Swivel-Fairlead
Standard	JIS	Material	Steel
Weight / Size	Sheave Dia.(mm) Dimension(mm) Mass Weight mm inch A B C D E F kg 19 3/4" 210 627 406 511 405 279 114 122 25 1 254 756 489 625 491 343 143 225 32 1-1/4" 305 816 508 714 470 434 160 304 38 1-1/2" 406 1018 641 921 533 545 216 658 44 1-3/4" 508 1201 724 1156 614 597 241 953 50 2 610 1343 762 1138 756 648 305 1202 57 2-1/4" 632 1515 1022 1543 769 800 330 2177 64 2-1/2" 762 1670 1016 1784 769 921 368 2722 76 3 1118 2739 1330 2642 1228 876 673 7484	Surface	Provide CCS , BV , LR , BV etc Certificate Customized service is available, Advanced equipment ,Strong consciousness in controlling quality Material:ZG230- 450,Q235 Surface:
Certificate	ABS , BV, mill certificate etc.	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Feature:

■ Specification:

Feature:

- 1.Excellent quality.
- 2.Competitive price .
- 3.Durable, long lifetime.

Fairlead is a device to change the cable direction used for guiding ropes in ship mooring and will not breakdown.

Provide CCS , BV , LR , BV etc Certificate

Customized service is available, Advanced equipment ,Strong consciousness in controlling quality

Material:ZG230-450,Q235

Surface: Blasting,Epoxy.

Machining facilities :CNC center, CNC lathes, ultrasonic wave cleaning,etc

Good wear and corrosion resistance

We can supply fairlead, roller according to JISF, DIN and GB standards. We can also make these products according to buyer's drawings.

Specification:

AF-40 360 Anchor Fairlead									
Wire Rope Dia.		Sheave Dia.(mm)	Dimension(mm)						Mass Weight
mm	inch		A	B	C	D	E	F	kg
19	3/4"	210	627	406	511	405	279	114	122
25	1	254	756	489	625	491	343	143	225
32	1-1/4"	305	816	508	714	470	434	160	304
38	1-1/2"	406	1018	641	921	533	545	216	658
44	1-3/4"	508	1201	724	1156	614	597	241	953
50	2	610	1343	762	1138	756	648	305	1202
57	2-1/4"	632	1515	1022	1543	769	800	330	2177
64	2-1/2"	762	1670	1016	1784	769	921	368	2722
76	3	1118	2739	1330	2642	1228	876	673	7484