

MARINE WINDLASS

36mm Anchor Windlass With CCS

36mm Anchor Windlass With CCS Main Parameter: Anchor Chain Diameter: 36mm(AM2)
Anchoring deepth: Less than 82.5m Working load: 55.1kn Overload: 82.7kn Holding Capacity:
329kn ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category Marine Windlass

Standard DIN

Material Cast steel

Certificate CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	36mm-Anchor-Windlass-With-CCS
Standard	DIN	Material	Cast steel
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 36mm Anchor Windlass With CCS
- Main Parameter:
- Remarks:

36mm Anchor Windlass With CCS

Main Parameter:

Anchor Chain Diameter: 36mm(AM2)

Anchoring deepth: Less than 82.5m

Working load: 55.1kn

Overload: 82.7kn

Holding Capacity: 329kn

Nominal speed: more than 9m/min

Hydraulic: HT3-2450C

Hydraulic motor: 63SCY14-1B

Motor model: Y225S-4, power: 37kw, 440v/60hz/3ph

Working pressure: 14.10Mpa

Flow rate: 77.68L/min

Remarks:

The distance between the two anchor lifter is 1830mm, can be adjusted by the client's requirement, the mooring drum is available for the windlass on the client requirement.