MARINE GENERATOR

4-stroke air-cooled gasoline engine

4-stroke air-cooled gasoline engine Parameter 4-stroke air-cooled gasoline engine Engine Model 154F 168F...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Generator
Standard	EN
Weight / Size	Brand SAE 15W/40(above CC grade) Lubrication method Splashing Ignition m...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Generator	**Model / SKU**	4-stroke-air-cooled-gasoline-engine
Standard	EN	**Weight / Size**	Brand SAE 15W/40(above CC grade) Lubrication method Splashing Ignition method Transistor electric, inductive firing Air cleaner Semi-dry, oil-immersed, foam filter element starting method Recoil start Transmission Threaded shaft/taper shaft/keyway shaft Pack Packing size(mm) 330x350x315 390x340x360 390x340x360 390x340x360 505x400x470 454x455x470 454x455x470 454x455x470 Net weight(Kgs) 10.8 15 16 16 25 33 33 34 Gross weight(Kgs) 12.8 17 18 18 27 35 35 36 20FT Qty 868 648 648 648 330 265 265 265 40FT Qty 1785 1326 1326 1326 685 530 530 530
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- 4-stroke air-cooled gasoline engine
- Parameter

4-stroke air-cooled gasoline engine

Parameter

4-stroke air-cooled gasoline engine

Engine	Model	154F	168F1	168F2	170F	173F	177F	188F	190F
	Type	Single cylinder,4-stroke,air-cooled OHV,gasoline engine							
	Bore x Stroke(mm)	54x38mm	68x45mm	68x54mm	70x54mm	73x58mm	77x58mm	88x64mm	90x66mm
	Displacement	87ml	163ml	196ml	208ml	242ml	270ml	389ml	420ml
	Compression ration	7.7:1	8.5:1	8.5:1	8.5:1	8.2:1	8.2:1	9.5:1	9.7:1
	Rated output power(3000rpm)	1.4kw	2.8kw	3.6kw	3.6kw	4.2kw	4.5kw	7.2kw	8.2kw
	Max.output power(3600rpm)	1.7kw	4.1kw	4.5kw	4.8kw	6kw	6.5kw	9.6kw	11.9kw
	Fuel consumption ratio	<450g/kw.h	<395g/kw.h	<395g/kw.h	<395g/kw.h	<390g/kw.h	<390g/kw.h	<374g/kw.h	<374g/kw.h
	Oil consumption ratio	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h	<6.8g/kw.h
	Fuel tank capacity	2.4L	3.6L	3.6L	3.6L	6.5L	6.5L	6.5L	6.5L
	Lubrication capacity	0.37L	0.6L	0.6L	0.6L	1.1L	1.1L	1.1L	1.1L
	Fuel tpe	90# automotive unleaded gasoline							
	Lube. Brand	SAE 15W/40(above CC grade)							
	Lubrication method	Splashing							
	Ignition method	Transistor electric, inductive firing							
	Air cleaner	Semi-dry, oil-immersed, foam filter element							
	starting method	Recoil start							
	Transmission	Threaded shaft/taper shaft/keyway shaft							
Pack	Packing size(mm)	330x350x315	390x340x360	390x340x360	390x340x360	505x400x470	454x455x470	454x455x470	454x455x470
	Net weight(Kgs)	10.8	15	16	16	25	33	33	34
	Gross weight(Kgs)	12.8	17	18	18	27	35	35	36
	20FT Qty	868	648	648	648	330	265	265	265
	40FT Qty	1785	1326	1326	1326	685	530	530	530