

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

CENTRIFUGAL PUMP

40CBZ-20 Self-priming Marine Pump

Applications: CBZ series self-priming marine pump is applicable for delivering water and other liquid which is like water in physicochemical properties.The maximum temperature of the liquid shall not be above ...

ISO9001 Supplier

Class Certificate


Export Supply



Key Highlights


Category	Centrifugal Pump
Standard	CB
Weight / Size	Model Capacity Q(m3/h) Head H(m) Efficiency (%) Speed (r/min) Power (kw)...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.




Technical Specifications

Category	Centrifugal Pump	Model / SKU	40CBZ-20-Self-priming-Marine-Pump
-----------------	------------------	--------------------	-----------------------------------



Standard	CB	Weight / Size	Model Capacity Q(m3/h) Head H(m) Efficiency (%) Speed (r/min) Power (kw) Allowable suction height (m) Weight (Kg) Motor
			32CBZ-21 8 21 35 2950 1.5 5 50
			Y90S-2H 32CBZ-30 8 30 36 2950
			2.2 5 55 Y90L-2H 32CBZ-42 8 42
			38 2950 4 5 73 YI12M-2H 40CBZ-
			20 12 20 58 2880 1.5 5 69 Y90S-
			2H 40CBZ-21 12 21 35 2950 2.2 5
			69 Y90L-2H 40CBZ-32 6.5 32 40
			2900 2.2 5 69 Y90L-2H 40CBZ-30
			12 30 40 2950 3 5 83 Y100L-2H
			40CBZ-42 12 42 40 2950 4 5 93
			Y112M-2H 50CBZ-21 21 21 45
			2950 3 5 79 Y100L-H 50CBZ-30
			21 30 45 2950 4 5 103 YI12M-2H
			50CBZ-32 20 32 65 2900 4 7 110
			Y112M-2H 50CBZ-35 14 35 55
			2900 4 7 110 YU2M-2H 50CBZ-42
			21 42 55 2950 5.5 5 116 Y132S1-
			2H 65CBZ-21 36 21 56 2950 4 5
			93 Y112M-2H 65CBZ-42 36 42 57
			2900 11 6 210 Y160M1-2H
			65CBZ-30 36 30 63 2900 5.5 6.5
			168 Y132S1-2H 65CBZ-50 24 50
			56 2900 7.5 6.5 160 Y132S2-2H
			65CBZ-60 36 60 56 2950 15 6 195
			Y160M2-2H 80CBZ-21 60 21 57
			2950 7.5 5.5 170 Y132S2-2H
			80CBZ-30 50 30 68 2900 7.5 6
			168 Y132S2-2H 80CBZ-42 60 42
			55 2900 15 5 207 Y160M2-2H
			80CBZ-50 30 50 58 2900 15 6 230
			Y160M2-2H 80CBZ-55 60 55 54
			2900 18.5 6 248 YI60L1-2H
			80CBZ-60 60 60 54 2950 22 6 280
			Y180M-2H 80CBZ-65 48 65 63
			2900 18.5 6 253 Y160L -2H
			80CBZ-70 60 70 63 2900 30 6 315
			Y200L1-2H 80CBZ-75 60 75 60
			2950 30 6 360 Y200L1-2H 80CBZ-
			25 25 25 58 1450 5.5 7 320
			Y132S-4H 100CBZ-20 90 20 73
			2900 11 6 240 Y160M1-2H
			100CBZ-21 100 21 65 2950 11 5
			280 YI60MI-2H 100CBZ-30 100 30
			68 2900 15 5 252 Y160M2-2H
			100CBZ-40 90 40 72 2900 18.5 5
			265 Y160L-2H 100CBZ-42 100 42
			62 2950 22 4.5 315 Y180M-2H
			100CBZ-50 60 50 68 2900 18.5 5



0.093870s

			5.5 290 Y160L-2H 100CBZ-60 100 60 66 2950 37 5 296 Y200L2-2H 100CBZ-65 100 65 70 2900 30 5.5 296 Y200LI-2H 100CBZ-80 100 80 70 2900 37 5.5 456 Y200L2-2H 100CBZ-85 100 85 67 2950 55 5 500 Y250M-2H 125CBZ-32 160 32 67 2950 30 5 421 Y200L1-2H 125CBZ-60 120 60 72 2900 37 6 480 Y200L2-2H 125CBZ-50 120 50 72 2900 30 5.5 420 Y200L1-2H 125CBZ-20 160 20 72 1450 18.5 5 420 Y180M-4H 150CBZ-20 200 20 75 1450 18.5 5 480 Y180M-4H 150CBZ-30 200 30 70 1450 37 7 490 Y225S-4H 150CBZ-45 200 45 70 1450 45 7 510 Y225M-4H 150CBZ-40 150 40 72 2900 30 5 480 Y200L1-2H 200CBZ-14 250 14 72 1450 18.5 7 480 Y180M-4H 200CBZ-45 300 45 71 1450 75 7 720 Y280S-4H 250CBZ-55 450 55 72 1450 110 5 844 Y315S-4H
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ Applications:

■ Meaning of CBZ model number:


Applications:

CBZ series self-priming marine pump is applicable for delivering water and other liquid which is like water in physicochemical properties. The maximum temperature of the liquid shall not be above 80°C.


CBZ series self-priming marine pump shall be used for water supply and discharging for ships.

Meaning of CBZ model number:

Model	Capacity Q(m ³ /h)	Head H(m)	Efficiency (%)	Speed (r/min)	Power (kw)	Allowable suction height (m)	Weight (Kg)	Motor
32CBZ-21	8	21	35	2950	1.5	5	50	Y90S-2H
32CBZ-30	8	30	36	2950	2.2	5	55	Y90L-2H
32CBZ-42	8	42	38	2950	4	5	73	Y112M-2H
40CBZ-20	12	20	58	2880	1.5	5	69	



40CBZ-21	12	21	35	2950	2.2	5	69	Y90L-2H
40CBZ-32	6.5	32	40	2900	2.2	5	69	Y90L-2H
40CBZ-30	12	30	40	2950	3	5	83	Y100L-2H
40CBZ-42	12	42	40	2950	4	5	93	Y112M-2H
50CBZ-21	21	21	45	2950	3	5	79	Y100L-H
50CBZ-30	21	30	45	2950	4	5	103	Y112M-2H
50CBZ-32	20	32	65	2900	4	7	110	Y112M-2H
50CBZ-35	14	35	55	2900	4	7	110	YU2M-2H
50CBZ-42	21	42	55	2950	5.5	5	116	Y132S1-2H
65CBZ-21	36	21	56	2950	4	5	93	Y112M-2H
65CBZ-42	36	42	57	2900	11	6	210	Y160M1-2H
65CBZ-30	36	30	63	2900	5.5	6.5	168	Y132S1-2H
65CBZ-50	24	50	56	2900	7.5	6.5	160	Y132S2-2H
65CBZ-60	36	60	56	2950	15	6	195	Y160M2-2H
80CBZ-21	60	21	57	2950	7.5	5.5	170	Y132S2-2H
80CBZ-30	50	30	68	2900	7.5	6	168	Y132S2-2H
80CBZ-42	60	42	55	2900	15	5	207	Y160M2-2H
80CBZ-50	30	50	58	2900	15	6	230	Y160M2-2H
80CBZ-55	60	55	54	2900	18.5	6	248	Y160L1-2H
80CBZ-60	60	60	54	2950	22	6	280	Y180M-2H
80CBZ-65	48	65	63	2900	18.5	6	253	Y160L-2H
80CBZ-70	60	70	63	2900	30	6	315	Y200L1-2H
80CBZ-75	60	75	60	2950	30	6	360	Y200L1-2H
80CBZ-25	25	25	58	1450	5.5	7	320	Y132S-4H
100CBZ-20	90	20	73	2900	11	6	240	Y160M1-2H
100CBZ-21	100	21	65	2950	11	5	280	Y160MI-2H
100CBZ-30	100	30	68	2900	15	5	252	Y160M2-2H
100CBZ-40	90	40	72	2900	18.5	5	265	Y160L-2H
100CBZ-42	100	42	62	2950	22	4.5	315	Y180M-2H
100CBZ-50	60	50	68	2900	18.5	5.5	290	Y160L-2H
100CBZ-60	100	60	66	2950	37	5	296	Y200L2-2H
100CBZ-65	100	65	70	2900	30	5.5	296	Y200LI-2H
100CBZ-80	100	80	70	2900	37	5.5	456	Y200L2-2H



100CBZ-85	100	85	67	2950	55	5	500	Y250M-2H
125CBZ-32	160	32	67	2950	30	5	421	Y200L1-2H
125CBZ-60	120	60	72	2900	37	6	480	Y200L2-2H
125CBZ-50	120	50	72	2900	30	5.5	420	Y200L1-2H
125CBZ-20	160	20	72	1450	18.5	5	420	Y180M-4H
150CBZ-20	200	20	75	1450	18.5	5	480	Y180M-4H
150CBZ-30	200	30	70	1450	37	7	490	Y225S-4H
150CBZ-45	200	45	70	1450	45	7	510	Y225M-4H
150CBZ-40	150	40	72	2900	30	5	480	Y200L1-2H
200CBZ-14	250	14	72	1450	18.5	7	480	Y180M-4H
200CBZ-45	300	45	71	1450	75	7	720	Y280S-4H
250CBZ-55	450	55	72	1450	110	5	844	Y315S-4H