

HIGH PRESSURE PUMP

430ZJ Marine High Pressure Injector Test Bench

ISO9001 Supplier

Class Certificate

Export Supply

430ZJ Marine High Pressure Injector Test Bench 430ZJ injector test bench is applicable to the low-speed injector test of B & W, su-lzer, man, government and other models. It is a necessary test equipment f...



Key Highlights

Category	High Pressure Pump
Standard	EN
Weight / Size	Number of picture(model) Name of parts Structural performance parameters...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	High Pressure Pump	Model / SKU	430ZJ-Marine-High-Pressure-Injector-Test-Bench
Standard	EN	Weight / Size	Number of picture(model) Name of parts Structural performance parameters 1 410ZJ-01-07-00 Box body kits Overall dimension(mm) 350x500x1085 2 430ZJ-01-04-00 Hand high pressure oil pump unit accemblage ø6 pluger rated pressure value (kg/cm2) 1600 ø14 pluger rated pressure value (kg/cm2) 600 3 SYP-1 Hand oil pump Rated pressure value (kg/cm2) 0-600 4 L9427(3)-07-04 Jack unit assemblage Piston diameter(mm) ø28.5 Piston stroke(mm) 120 Working pressure of oil cylinder(kg/cm2) 600 Max stroke(mm) 133 Max withstan weight(t) 5 5 Weight 130kg Packing size(mm) 880x880x1320
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ 430ZJ Marine High Pressure Injector Test Bench	■ Specification:
----------	--	------------------

430ZJ Marine High Pressure Injector Test Bench

430ZJ injector test bench is applicable to the low-speed injector test of B & W, su-lzer, man, government and other models. It is a necessary test equipment for coastal passenger and cargo ships and ocean going ships. The test bench can also adjust the opening pressure of cylinder head safety valve and fuel injection pump safety valve with the help of some accessories, and disassemble the fuel injector nut.

The test bench is mainly composed of box, manual high-pressure oil pump assembly, kilogram assembly, hydraulic manual pump, high-pressure oil pump assembly, pressure gauge, etc. At present, equipped with medium speed engine injector clamp, it can be expanded to be applicable to NVD, 300, 350 and other series of injector tests.

Specification:

No.	Number of picture(model)	Name of parts	Structural performance parameters	
1	410ZJ-01-07-00	Box body kits	Overall dimension(mm)	350x500x1085
2	430ZJ-01-04-00	Hand high pressure oil pump unit accemblage	ø6 pluger rated pressure value (kg/cm2)	1600
			ø14 pluger rated pressure value (kg/cm2)	600

3	SYP-1	Hand oil pump	Rated pressure value (kg/cm2)	0-600
4	L9427(3)-07-04	Jack unit assemblage	Piston diameter(mm)	φ28.5
			Piston stroke(mm)	120
			Working pressure of oil cylinder(kg/cm2)	600
			Max stroke(mm)	133
			Max withstan weight(t)	5
5	Weight	130kg	Packing size(mm)	880x880x1320