


FIRE HYDRANT

45 Degree PN16 Flanged Fire Hydrant

Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm ...

- ISO9001 Supplier
- Class Certificate
- Export Supply



Key Highlights

| | |
|--------------------|---|
| Category | Fire Hydrant |
| Standard | Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(... |
| Material | Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

| | | | |
|--------------------|--|--------------------|--|
| Category | Fire Hydrant | Model / SKU | 45-Degree-PN16-Flanged-Fire-Hydrant |
| Standard | Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(BSP) 50mm 165 200 105 Brass Bronze BS5154:1991 2 1/2" 65mm 2 1/2"(BSP) 65mm 185 230 140 Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling. | Material | Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(BSP) 50mm 165 200 105 Brass Bronze BS5154:1991 2 1/2" 65mm 2 1/2"(BSP) 65mm 185 230 140 Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling. |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty | 12 Months unless specified otherwise |
| Origin | China | | |

China 45 Degree PN16 Flanged Fire Hydrant:

| Water Inlet | Water Outlet | D(mm) | H(mm) | L(mm) | Material | Standard |
|----------------|---------------------|-------|-------|-------|-----------------|-------------|
| 2" 50mm | 2"(BSP) 50mm | 165 | 200 | 105 | Brass Bronze | BS5154:1991 |
| 2 1/2" 65mm | 2 1/2"(BSP) 65mm | 185 | 230 | 140 | | |

Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling.