FIRE HYDRANT

45 Degree PN16 Flanged Fire Hydrant

Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Fire Hydrant
Standard	Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(...
Material	Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Fire Hydrant	**Model / SKU**	45-Degree-PN16-Flanged-Fire-Hydrant
Standard	Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(BSP) 50mm 165 200 105 Brass Bronze BS5154:1991 2 1/2" 65mm 2 1/2"(BSP) 65mm 185 230 140 Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling.	**Material**	Water Inlet Water Outlet D(mm) H(mm) L(mm) Material Standard 2" 50mm 2"(BSP) 50mm 165 200 105 Brass Bronze BS5154:1991 2 1/2" 65mm 2 1/2"(BSP) 65mm 185 230 140 Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

China 45 Degree PN16 Flanged Fire Hydrant:

Water Inlet	Water Outlet	D(mm)	H(mm)	L(mm)	Material	Standard
2" 50mm	2"(BSP) 50mm	165	200	105	Brass Bronze	BS5154:1991
2 1/2" 65mm	2 1/2"(BSP) 65mm	185	230	140		

Suitable for equip with China type , Storz type , John Morris type, Nakijima type hose coupling.