MOORING ROPE

6 Strand Polyamide Rope

ISO9001 Supplier

Class Certificate

Export Supply

6 Strand Polyamide Rope Structure: 6 strand Density:1.14, sinking in water. Melt point:215 centigrade Elongation rate: 15% to 25% Good abrasion resistance and good corrosion assistance. ...



Key Highlights

Category	Mooring Rope
Standard	EN
Material	Polyamide
Certificate	CCS,BV,ABS,LR etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Mooring Rope	**Model / SKU**	6-Strand-Polyamide-Rope
Standard	EN	**Material**	Polyamide
Certificate	CCS,BV,ABS,LR etc.	**Warranty**	12 Months unless specified otherwise
Origin	China		

China 6 Strand Polyamide Rope:

6 Strand Polyamide Rope

Structure: 6 strand

Density:1.14, sinking in water.

Melt point:215 centigrade

Elongation rate: 15% to 25%

Good abrasion resistance and good corrosion assistance.

Diameter	Circumference		Linear Density		Breaking Strength		
mm	Inch	mm	Inch	Ktex	lb/foot	Tons	KN
28	1-1/8	87.92	3-1/2	495	0.333	15.92	156
32	1-5/16	100.48	4	640	0.43	20.1	197
36	1-1/2	113.04	4-1/4	815	0.548	25.1	246
40	1-5/8	125.6	5	1010	0.679	30.2	296
44	1-3/4	138.16	5-1/2	1260	0.847	36.12	354
48	2	150.72	6	1450	0.974	42.35	415
52	2-1/8	163.28	6-1/2	1690	1.136	49.18	482
56	2-1/4	175.84	7	1970	1.324	56.43	553
60	2-1/2	188	7-1/2	2250	1.512	64.39	631
64	2-5/8	201	8	2570	1.727	72.65	712
72	3	226	9	3250	2.184	90.71	889
80	3-1/8	251	10	4020	2.702	110.92	1087
88	3-1/2	276	11	4870	3.273	132.24	1296
96	3-3/4	302	12	5790	3.891	166.53	1632